



LARIUS MIRO K21565 AIRLESS ELECTRIC PUMP

Reference:

LARIUS MIRO K21565 AIRLESS ELECTROPOMPAINTING PUMP

LARIUS MIRO K21565 is an airless electric paint pump for use in high pressure without the aid of air (hence the term AIRLESS), capable of delivering a maximum flow rate of 2.2 l/m.

LARIUS MIRÒ K21565 is a high-pressure electric pump equipped with the exclusive electric piloting system that allows the safeguard of the motor and of the board, in case of lack of grounding, sudden changes of tension, overheating and inadequate electric extensions.

LARIUS MIRÒ K21565 is able to apply in total efficiency in the aspiration and application of dense and viscous products, in addition thanks to the airless technology the drying times are considerably reduced, this allows the lesser contribution of diluting liquids to the product.

Thanks to LARIUS MIRÒ K21565, the coating process will be quicker and less time-consuming; in fact, it makes it possible to cover the entire area of application with fewer passes.

All the components that characterize the LARIUS MIRÒ K21565 pump are of high quality and make it extremely resistant to wear and tear. This version of the LARIUS MIRÒ electric pump includes a practical tank with a maximum capacity of 6 litres for the containment of the material to be nebulized, in this way the use will be even simpler and more immediate.

TECHNICAL CHARACTERISTICS LARIUS MIRO K21565

Electropump for airless painting
frame version
Tank capacity: 6 l
Max flow rate: 2.2 l/m
Motor power: 750 Watt
Maximum pressure: 250 bar
Power supply: 230 V
Frequency: 50 Hz
Available voltages: 115 VAC - 60 Hz and 400 VAC - 50 Hz
Spray guns included: 1 AT 250 gun
Nozzle size: Up to 0.019"
Minimum generator power to match: minimum 4.0 KW Single phase
Length: 400 mm
Width: 400 mm
Height: 900 mm
Dry weight: 23 Kg

Looking for an electric pump with different features? [Here](#) you can find the whole range of LARIUS or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Net power (kW)	
Pump type	
Fluid type	
Maximum output capacity (Lt/min)	
Pressure (bars)	
Tank capacity (L)	6
Length (mm)	400
Width (mm)	400
Height (mm)	600
Maximum paint flow rate (Lt/min)	
Number paint colors	1
Feed Type	Single-Phase
Number of guns supported	1
Nozzle's largest diameter	
Version	Trolley
Type of pumping group	Membrane
Product type	Pompa
Weight (Kg)	