

## Super-silenced vehicular generator 16 KW

Reference: GVSS16KW



### Super-silenced 11 KW vehicular generator

Single-phase vehicular generator of 16 KW with Lombardini engine powered by diesel of 3000 rpm with soundproof capsule and **supersilenced**. The single phase vehicular generator has an electric start.

The alternator of the single phase vehicular generator is synchronous, brushless and water cooled (in stainless steel AISI 316 L jacket). The vehicular generator thanks to its casing is very silent in fact it has acoustic emissions of only 56 dB (A). Designed with high quality components it has a low fuel consumption: only 0.35 Lt/KW/h. The engine cooling pump is an electric pump.

**Remote control and control** of single-phase vehicular generator with:

- Hour meter
- Load indicator
- Automatic stop for low oil pressure and water over-temperature
- Starter motor release
- Quick connector and 15 meters of cable

#### **Technical features:**

Single-phase continuous use power: 16 KW

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Motor: Lombardini LDW1404

Starting: Electric

Consumption: 0.35 Lt/KW/h

Length: 1070 mm

Width: 580 mm

Height: 650 mm

Weight: 290 Kg

From 4 KW and up, the vehicular gensets in this range are the quietest, **compact** and **lightweight** for the same performance. These vehicle gensets are the quietest, plus vibrations are kept to a minimum, making gensets like this **always competitive** in the marketplace.

If you are looking for a product similar to the vehicle generator, we recommend that you browse our extensive catalog of [vehicle generators](#). So you can find the product that best suits your needs and perfect for your vehicle.

Images and technical data are not binding.

### Technical Sheet

Phase	Single phase
Continuous power single phase (KW)	16
Continuous power single phase (KVA)	18
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Lombardini LDW1404
Engine rpm (rpm)	3000
Starting system	Electric
Number cylinders	4
Cooling	Water
Alternator	Synchronous, brushless
Consumption (L/h)	0.35
Acoustic pressure	56 dB(A) at 7 m
Length (mm)	1070
Width (mm)	580
Height (mm)	650
Dry weight (Kg)	290
Silenced	Yes
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	No
Engine manufacturer	Lombardini