



ULTIMATE75-S300SA-250 UNDERWATER LED SPOTLIGHT FLUSH STAINLESS STEEL

Reference: ULTIMATE 75-S300+SA250

ULTIMATE75-S300SA-250 LED spotlight

ULTIMATE75-S300SA-250 is an underwater LED spotlight for boats capable of generating a light output of 250W in Stainless Steel and borosilicate glass.

ULTIMATE75-S300SA is an underwater spotlight for welding in steel or aluminum hulls. The ULTIMATE75-S300SA gives you the possibility to do maintenance and upgrades without the need to take the boat dry, this will give you the possibility to perform constant maintenance increasing the life of the spotlights.

ULTIMATE75 is equipped with SA (Super Adjustable) internal unit allows you to vary the beam angle from narrow to wide and universally move the beam direction 20 degrees from inside the projector housing.

It is recommended that the light be installed 250 mm below the minimum waterline when the yacht is loaded with 50% fuel and 50% water and that the light be angled 15 degrees downward.

The ULTIMATE75SA underwater spotlight has a larger aperture that increases light output by 25%.
ULTIMATE75-S300SA-250 comes standard with Ice Class Lloyds, GL certification and has been pressurized to 80 bar.

The ULTIMATE75-S00SA underwater spotlight can be supplied in three different designs:

- ULTIMATE75-S300SA for a flush installation angle
- ULTIMATE75-S330SA for a 30° installation angle
- ULTIMATE75-S350SA for a 50° installation angle

TECHNICAL FEATURES ULTIMATE75-S300SA

Hull Material: Stainless steel and aluminum
Boat Size: Up to 30 m
Transom Spacing: 1.5-2.0 m
P & S Spacing: 1.5-5 m
Beam Angle: 65° / 77° / 100°

Maximum Power: 250 W
Lumens: 19000
Typical LED Life Expectancy: 3000 h
Minimum and Maximum Operating Voltage: 110-240V AC
Current / Amplifier: 1.4 - 0.7 A
Drive Type: External
Output Drivers: N/A
Output Control: On / Off

Device Length: 250 - 306 mm
Device Diameter: 120 - 140 mm
Device Profile: N/A
Required Removal Space: 170 mm
Total Weight: 6.3 - 9.5 Kg
Cut Hole: N/A
Material: Stainless Steel
Growth Resistant Lens: Borosilicate Glass

Looking for an Underwater spotlight with different features? [Here](#) you can find the section dedicated to nautical lighting systems with brands specializing in the sector.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Voltage (V)	110-240
Diameter (Ø)	120 - 140 mm
Power (W)	250
Average life of LEDs (hrs)	3000
Type of lamps	LED
Length (mm)	250 - 306
Weight (Kg)	6.3 - 9.5
Video	mSzY-vFJivE