



LINZ G-TS20C PTO UNIT 20KVA

Reference: PEDROLLO G-TS20C

PEDROLLO G-TS20C 20KVA PTO SHAFT GENERATOR

PEDROLLO G-TS20C 20KVA single-three phase PTO shaft generator with 430rpm tractor connection. The PEDROLLO G-TS20C shaft-driven generator has a voltage of 230 / 400 V and a frequency of 50 Hz.

The E1S13MF /4 alternator of the PEDROLLO G-TS20C PTO shaft generator has a compound voltage regulator. The compound regulator allows you to stabilize the voltage and avoid damage to the connected sensitive devices.

The PEDROLLO G-TS20C easy to transport, install and position due to its compact size, this model is ideal for mounting on a tractor unit. The PEDROLLO G-TS20C PTO shaft generator has a tractor power requirement of 60 HP and a PTO speed of 430 rpm.

All alternators are equipped with a standard electrical panel which includes: Voltmeter, Ammeter, Frequency meter, CEE 5P socket, CEE 3P 16 or 32 Amp socket, Schuko socket with thermal protection, circuit breaker and earth leakage breaker.

The PEDROLLO G-TS20C must be used after being placed on the ground. After connecting the tractor PTO to the gearbox via PTO shaft, the tractor PTO must be set to the required speed.

The overdrive, by transmitting the mechanical power of the tractor PTO to the alternator, increases the required PTO speed up to the nominal speed of the alternator. Perfect operating conditions are reached when the frequency meter indicates the value of 50Hz.

Technical Features of the PEDROLLO G-TS20C:

Phase Type: Single Phase / Three Phase
Continuous Power: 20 KVA
Continuous Power: 20 KW
Voltage: 230 / 400 V
Frequency: 50 Hz
PTO Power i output (rpm required 540): 33. 6HP
Tractor power required: 60 HP
PTO RPM: 430 rpm
Alternator: E1S13MF /4
Voltage regulator: Compound
Length: 1152 mm
Width: 960 mm
Height: 1025 mm
Weight: 194.5 Kg

Are you looking for a PTO shaft generator with different technical features? [Here](#) you can find the full range of PEDROLLO PTO

generators or other brands specializing in this field.

Images and technical data are not binding and may be subject to manufacturer's revisions.

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	20
Maximum power single phase (KVA)	20
Frequency (Hz)	50
Voltage (V)	230 / 240
Sockets configuration	CEE 5P, CEE 3P 16 o 32 Amp, Schuko
PTO speed (round/min)	430
Required tractor power	60 HP
Length (mm)	1152
Width (mm)	960
Height (mm)	1025
Dry weight (Kg)	194.5
Voltage regulator	Compound