



AIRSTAR FLEX L HTI 4X1000W

Reference: SIR0366 - 10-36-023x4

AIRSTAR FLEX L HTI 4X1000W

AIRSTAR FLEX L HTI 4X1000W is a lightglobe equipped with 4 HTI lamps capable of delivering a total light output of 4000W, thanks to which it can illuminate an area of 22500 m².

AIRSTAR FLEX L HTI 4X1000W is a Lightglobe specially designed to be used on semi-permanent installations and for long periods of time, it consists of a semi-rigid envelope that once unfolded keeps its shape.

The HTI Lamps (Hydrargyrum Tageslicht Iodide) is able to illuminate in daylight a very large area, in addition it has been designed to be, intense lights, they are short arc lamps with maximum luminance and anti-glare system.

AIRSTAR FLEX L HTI 4X1000W comes complete with telescopic pole made of corrosion and rust resistant chromed steel. The telescopic pole can reach a height of 5.30 m and can support a maximum weight of 40 kg, in addition to giving excellent stability to the lightglobe even in unfavorable conditions with winds up to 100 Km / h.

AIRSTAR FLEX L HTI 4X1000W is supplied with a chrome-plated steel pole resistant to corrosion and rust.

TECHNICAL FEATURES AIRSTAR FLEX L HTI 4X1000W:

Envelope diameter: 140 cm
Maximum pole height: 5.30 m
Color temperature: 4000 K
Number of lamps: 4
Lamp type: HTI
Lamp power: 1000 W
Frequency: 50 Hz
Power supply voltage: 230 V
Lighting area for activities at the first level of risk (standard EN12464-2): 4700 m²
Lighting area open space environment (standard EN1838): 22500 m².
Lighting under the balloon (placed at 7 meters): 600 Lx
Luminous flux: 440000 Lm
Global protection class: IP 54
Open size: Ø 1650 x 5300 mm
Balloon weight: 27 Kg
Telescopic pole weight: 16 Kg

Looking for a Lightglobe with different technical features? [Here](#) you can find the full range of Lightglobe AIRSTAR or other specialized brands.

Images and technical data not binding.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Protection degree	IP54
Maximum height (m)	5.3
Type of lamps	Htl
Lamps	4 x 1000 W
Telescopic pole	Acciaio cromato
Illuminated area (m ²)	22500
Total lumens (Lm)	440000
Open size (mm)	Ø 1650 x 5300
Video	1bZH1bIIPWA