



NANNI QMS7.5M MARINE GENERATOR 7.5KW

Reference: QMS 7.5M

NANNI QMS7,5M MARINE GENERATOR 7.5KW

NANNI QMS7,5M is a three-phase marine generator equipped with a Kubota engine, 4 strokes with Diesel power supply capable of delivering a maximum power of 7.5KW.

The cooling system allows the NANNI QMS7,5M to work at an optimal temperature. In the case of a closed circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. In a Keel Cooling system, engine heat is dissipated by passing coolant through pipes embedded in the hull. The NANNI QMS7,5M marine generator comes equipped with a Super Glow system for starting in cold temperatures without the risk of sudden engine failure.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS7.5M is improved, resulting in low fuel consumption.

NANNI QMS7.5M is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

TECHNICAL FEATURES NANNI QMS7,5M

Phase Type: Single Phase
Maximum Power: 7.5 KW
Continuous Power: 6.6 KW
Maximum Power: 7.5 KVA
Continuous Power: 6.6 KVA
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Engine: Kubota, 3-stroke
Start: Electric
Isolation Class: H
Protection Class: IP23
Consumption: 2.5 Lt/h at full load
Length: 840 mm
Width: 489 mm
Height: 620 mm
Weight: 224 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7.5
Continuous power single phase (KW)	6.6
Maximum power single phase (KVA)	7.5
Continuous power single phase (KVA)	6.6
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Kubota, 4 stroke
Engine rpm (rpm)	1500
Starting system	Electric
Number cylinders	3
Cylinders' position	In line
Cooling	Water
Inyección	Indirect (E-TVCS)
Alternator	Electronic regulator
Consumption (L/h)	2.5 at 100% of the load
Length (mm)	840
Width (mm)	489
Height (mm)	620
Dry weight (Kg)	224