



## BLACK+DECKER BXGNI2200E SINGLE PHASE INVERTER GENERATOR 2 KW

Reference: BXGNI2200E

### BLACK+DECKER BXGNI2200E 2KW GENERATOR

BLACK+DECKER BXGNI2200E is a 2KW Single Phase Generator with a 4-stroke 114cc gasoline-powered engine, compact and easy to use.

The BLACK+DECKER BXGNI2200E generator is equipped with an alternator with AVR regulation, and is ideal for all electronic devices thanks to the Inverter technology.

The single-phase generator BLACK+DECKER BXGNI2200E is equipped with manual recoil starter, in addition this generator has a low fuel consumption, in fact it can guarantee an autonomy of 3.2 hours at full load.

BLACK+DECKER BXGNI2200E thanks to its only 19kg and an extremely compact body, the use and handling of this machine will be extremely simple. Thanks to its characteristics it easily adapts to various uses such as homes, mobile homes, campsites, hobbies, construction sites, etc..

Thanks to the inverter technology and the AVR voltage regulator of the latest generation, the generator is super silenced, BLACK+DECKER BXGNI2200E in fact has a noise emission of only 92 dB (A).

The single-phase generator BLACK+DECKER BXGNI2200E is equipped with a front panel consists of 2 Schuko sockets with 230V power supply with pure sine wave, 1 cigar lighter and 2 USB 5V DC sockets.

#### TECHNICAL CHARACTERISTICS BLACK+DECKER BXGNI2200E:

Type of phase: Single-phase  
Maximum power: 2,2 KW  
Continuous power: 2 KW  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: 4 Strokes 114 cc  
Starting: Manual recoil starter  
Voltage regulator: AVR  
Tank capacity: 4.1 Lt  
Autonomy: 3.2 h at 100% load  
Length: 555 mm  
Width: 320 mm  
Height: 465 mm  
Weight: 19 Kg

Discover the full range of [generator](#) brand BLACK+DECKER or other top brands, browse our catalog to find the one that best suits

your needs.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.2
Continuous power single phase (KW)	2
Maximum power single phase (KVA)	2.2
Continuous power single phase (KVA)	2
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	4 stroke
Emissions Regulations	Stage 5
Starting system	Pull starter with recoil
Engine capacity (cm <sup>3</sup> )	114
Fuel tank capacity (L)	4.1
Running time (h)	3.2
Acoustic power	92 dB(A)
Length (mm)	555
Width (mm)	320
Height (mm)	465
Dry weight (Kg)	19
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR + Inverter
Video	tSPuKCWYbE4