



BLACK+DECKER BXGND7900E SINGLE-THREE PHASE GENERATOR 7,5KVA

Reference: BXGND7900E

BLACK+DECKER BXGND7900E GENERATOR SINGLE/THREE-PHASE 7,5KW

BLACK+DECKER BXGND7900E is a 7,5KW single/three-phase Generator with a 498cc 4-stroke Diesel-powered engine, compact and easy to use.

The BLACK+DECKER BXGND7900E features an AVR regulated alternator, perfect for use with power tools, gardening, outdoor activities or as an emergency generator.

The BLACK+DECKER BXGND7900E single/three phase comes with electric start and ATS control panel connectors, giving you the ability to connect the generator to the grid as an emergency power pack.

The BLACK+DECKER BXGND7900E has a low fuel consumption and an extremely capacious tank, capable of holding up to 12L, thanks to these features the generator provides a range of 9 hours at full load.

BLACK+DECKER BXGND7900E thanks to its only 160kg and a body equipped with handles and wheels, it will be extremely easy to move and use for any activity you want to assign this generator.

The BLACK+DECKER BXGND7900E single-phase generator is equipped with a frontal electric panel composed of a digital display with hour meter, differential \dot{u} , connector for ATS panel and a practical Switch for single-phase or three-phase operation. The generator is also equipped with a socket panel, complete with:
1 socket 32A 3P, 1 socket 32A 5P 2 Schuko sockets with 230Vac power supply.

TECHNICAL CHARACTERISTICS BLACK+DECKER BXGND7900E:

Type of phase: Single-phase / Three-phase
Maximum power: 7,9 KVA
Continuous power: 7,5 KVA
Maximum power: 5.7 KW
Continuous power: 5,4 KW
Fuel: Diesel
Voltage: 230 / 400 V
Frequency: 50 Hz
Engine: 4 Strokes 498 cc
Starter: Electric with battery / Automatic
Voltage regulator: AVR
Tank capacity: 12 Lt
Autonomy: 9 h at 100% load
Length: 960 mm
Width: 560 mm
Height: 790 mm

Weight: 160 Kg

Discover the full range of [generator](#) brand BLACK+DECKER or other top brands, browse our catalog to find the one that best suits your needs.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	5,7
Continuous power single phase (KW)	5,4
Maximum power single phase (KVA)	7,9
Continuous power single phase (KVA)	7,5
Maximum power three phase (KW)	5,7
Continuous power three phase (KW)	5,4
Maximum power three phase (KVA)	7,9
Continuous power three phase (KVA)	7,5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	4 Tempi
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	498
Cooling	Air
Fuel tank capacity (L)	12
Running time (h)	9
Length (mm)	960
Width (mm)	560
Height (mm)	790
Dry weight (Kg)	160
Silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	BLACK+DECKER

Video

MnzG-Ezghl
