



MOSA GE 7000 KBM SINGLE PHASE GENERATOR 6,7KVA STAGE V

Reference:

MOSA GE 7000 KBM SINGLE-PHASE GENERATOR 6,7KVA STAGE V

MOSA GE7000 KBM is a single-phase generating set with a gasoline-powered engine capable of delivering a power of 6KW. The MOSA GE7000 KBM generating set is equipped with manual recoil starter. The MOSA GE7000 KBM generator set alternator is synchronous, single phase, self-excited, self-regulated, brushless and with class H insulation.

MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 76 kg as well as its practical tubular handles.

The MOSA GE7000 KBM generator set with 6.1-liter tank has a fuel consumption of 2.4 liters/hour at 75% load for an autonomy of up to 2 hours.

The control panel is composed of:

- Output sockets: 1x 230V 32A 2P+E CEE / 1x 230V 16A 2P+E CEE
- Thermal circuit breaker for socket protection 230V/16A
- Voltmeter
- Thermomagnetic circuit breaker
- Earth terminal (PE)

Technical specifications MOSA GE7000 KBM :

Single-phase continuous use power: 5 KW

Single-phase continuous use power: 5.5 kVA

Maximum single-phase power: 6 KW

Maximum single-phase power: 6.7 kVA

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Motor: KOHLER CH440

Start: Manual Rewind

Consumption: 2.4 Lt/h at 75% load

Acoustic power measured LwA: 97 dB(A) (71 dB(A) @ 7m)

Length: 770 mm

Width: 520 mm

Height: 650 mm

Weight: 76 Kg

If you are looking for another product like the MOSA GE7000 KBM generator set then you can check out our catalog for other [land based generator sets](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	6
Continuous power single phase (KW)	5
Maximum power single phase (KVA)	6.7
Continuous power single phase (KVA)	5.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE
Engine	KOHLER CH440
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Ignition	Recoil
Starting system	Pull starter
Engine capacity (cm ³)	389
Number cylinders	1
Oil capacity (L)	1.1
Cooling	Air
Alternator	Sincrono, autoeccitato, autoregolato, senza spazzole
Bore x stroke (mm)	88 x 64
Length (mm)	770
Width (mm)	520
Height (mm)	650
Dry weight (Kg)	76
Silenced	No
Compression ratio	8.2 : 1
ATS Switch device	No ATS
Voltage regulator	Capacitor
Engine manufacturer	Kohler