



MOSA GE SX-12054 KDT STAGEV

Reference: CM4S00U3

MOSA GE SX-12054 KDT 8.8 KW

MOSA GE SX-12054 KDT three-phase generator set of 8.8 KW with KOHLER KDW702 diesel engine. The MOSA GE SX-12054 KDT generator set is equipped with electric starter. The alternator of the MOSA GE SX-12054 KDT generator set is synchronous, three-phase, self-excited, self-regulated with class H insulation.

This MOSA GE SX-12054 KDT generator set is compact and easy to handle and transport thanks to its compact size, its weight of 350 kg as well as the practical central hook for lifting. Generator with canopy to reduce noise emissions which makes it super silent.

The MOSA GE SX-12054 KDT generator with 38 litre tank has a fuel consumption of 2.6 litres/hour at 75% load for an autonomy of more than 14 hours.

Sockets:

1x 400V 16A 3P+N+T CEE
2x 230V 16A 2P+T Schuko

Technical specifications:

Maximum power three-phase: 8.8 KW
Continuous use power three-phase: 8 KW
Maximum power three-phase: 11 KVA
Continuous use power three-phase: 10 KVA
Single-phase continuous use power: 7 KW
Single-phase continuous use power: 7 KVA
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Engine: KOHLER KDW702
Starting: Electric
Consumption: 2.6 Lt/h at 75% load
Length: 1568 mm
Width: 710 mm
Height: 1115 mm
Weight: 350 Kg
Supersilenced

MOSA generator set GE SX-12054 KDT portable - KOHLER KDW702 diesel engine electric start - Three-phase alternator

If you are looking for another product such as the MOSA GE SX-12054 KDT generator set then you can consult our catalogue for other [terrestrial generator sets](#).

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service does not assume responsibility for any changes made by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	7
Continuous power single phase (KVA)	7
Maximum power three phase (KW)	8.8
Continuous power three phase (KW)	8
Maximum power three phase (KVA)	11
Continuous power three phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A 3P+N+T CEE IP67 - 2 x 230V 16A 2P+T Schuko IP68
Engine	KOHLER KDW702
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	686
Number cylinders	2
Oil capacity (L)	1.6
Cooling	Water
Alternator	Synchronous self-excited, self-regulated
Bore x stroke (mm)	75 x 77.6
Fuel tank capacity (L)	38
Consumption (L/h)	2.6
Running time (h)	14.5
Acoustic power	93 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	1568
Width (mm)	710
Height (mm)	1115

Dry weight (Kg)	350
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Kubota
