



## MASE IS 24 K SINGLE PHASE MARINE GENERATOR 26KW

Reference: MASE IS24 K

### MASE IS 24 K SINGLE-PHASE MARINE GENERATOR 26KW

MASE IS24K single-phase marine generator with KUBOTA V3300 engine with diesel power supply at 1500 rpm capable of delivering a power of 26KW.

The MASE IS24K marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS24K marine generator is built with KUBOTA diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS24K.

The soundproof cabin of the MASE IS24K consists of a load-bearing structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely light and very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the genset installed in narrow spaces.

#### Technical features:

Maximum power Single-phase: 26 KW

Continuous use power Single-phase: 24 KW

Fuel: Diesel

Voltage: 115 V / 230 V

Frequency: 50 Hz

Motor: KUBOTA V3300

Length: 1260 mm

Width: 640 mm

Height: 830 mm

Weight: 630 Kg

If you are looking for another generator like the MASE IS24K then you can browse the entire catalog of [marine gensets](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	26
Continuous power single phase (KW)	24
Maximum power single phase (KVA)	26
Continuous power single phase (KVA)	24
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	115 / 230
Engine	KUBOTA V3300-BG
Engine rpm (rpm)	1500
Speed governor	Electronic
Engine capacity (cm <sup>3</sup> )	3318
Number cylinders	4
Cooling	Air / water (Intercooler W/A)
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Compression ratio	18 : 1
Lubrication	Forced
Acoustic pressure	52 dB(A) at 7 m
Length (mm)	1260
Width (mm)	640
Height (mm)	830
Dry weight (Kg)	630
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Kubota