

## GENERAC DF 7500 DUST FIGHTER 40mq

Reference: DS01E0L-0000GB



## GENERAC DF 7500 DUST FIGHTER 40mq

GENERAC Dust Fighter DF7500 is a dust suppression system with a maximum flow rate of 40 meters, ideal for small to medium sized work areas.

GENERAC Dust Fighter DF7500 aims to solve in the most efficient way the problem of volatile dust abatement in all environments where it is necessary to contain the emission of dust into the atmosphere.

Thanks to the system of nebulization of water particles up to 180 microns the Dust Fighter GENERAC dust particles bind and end up on the ground more easily. In addition, the atomization method allows you to completely cover the dust cloud saving you significant amounts of water.

GENERAC DF7500 comes complete with:

- Integrated control panel
- Phase inverter
- Booster pump with peripheral impeller
- Flow meter for pump protection
- Pressure gauge for outlet pressure reading
- Stainless steel crown with nozzles
- 2 wheels, tow hitch and forklift pockets
- 2 height-adjustable stabilizers

### TECHNICAL FEATURES GENERAC DF7500

Electrical motor power (fan): 7.5KW  
Coverage (without wind): 30 - 40 sqm  
Electrical connection: Three-phase outlet - 32 A  
Water connection: STORZ / CAMLOCK  
Min inlet pressure: 1 bar  
Water consumption: 52 l/min  
Water inlet filter: 180 micron  
Working angle: 335°  
Inclination: 0° / 40°  
Width: 3300 mm  
Length: 1830 mm  
Height: 2180 mm  
Dry weight: 760 Kg

Looking for a Dust Fighter with different technical characteristics? [Here](#) you can find the whole range of Generac or other

specialized brands.

Images and technical data are not binding and may be subject to revision by the manufacturer.

## Technical Sheet

Sockets configuration	1 x 400 V -32 A
Power (kW)	7.5
Throwing distance (m)	40
Maximum output capacity (Lt/min)	52
Length (mm)	3300
Width (mm)	1830
Height (mm)	2180
Dry weight (Kg)	760