



GREEN POWER GP 22 TR-C THREE-PHASE PTO GENERATOR 20KVA

Reference: 00805

GREEN POWER GP 22 TR-C SINGLE-PHASE / THREE-PHASE PTO GENERATOR 20KVA

Generator GREEN POWER GP22 TR-C single / three-phase PTO complete with MECC ALTE BTP3-2L/2 alternator capable of delivering a power of 20KVA

The GREEN POWER GP22 TR-C generator is very reliable as it has been built and designed using top quality materials. The PTO generator is easy to transport, install and position due to the compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 40 HP and a PTO speed of at least 430 rpm.

These compact, robust and easy-to-use generators come complete with a 3-point hitch base for secure attachment to any tractor. The GREEN POWER GP22 TR-C generator is equipped with IP44 panel with magneto-thermal switch socket, differential, 32A 230V socket, 16A 230V Schuko socket and E31 digital module complete with: voltmeter, frequency meter and counter.

TECHNICAL FEATURES PTO GENERATOR GREEN POWER GP22 TR-C

Phase type: Singlephase / Threephase
Threephase maximum power: 22 KVA / 17.6 KW
Threephase continuous power: 20 KVA / 16 KW
Voltage: 230 - 400 V
Frequency: 50 Hz
Engine rpm: 3000 rpm
Necessary tractor power: 40 hp
PTO speed: 430 rpm
Alternator: MECC ALTE BTP3- 2L / 2 (OR QUIVALENT)
N° of poles: 2
Insulation class: H
Protection class: IP 23
Voltage regulator: Compound
Length : 805 mm
Width: 580 mm
Height: 915 mm
Weight: 139 Kg

Are you looking for a PTO generator with different technical features? [Here](#) you can find the full range of Green Power or other brands specializing in the field

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	17.6
Continuous power three phase (KW)	16
Maximum power three phase (KVA)	22
Continuous power three phase (KVA)	20
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine rpm (rpm)	3000
Alternator	MECC ALTE T20F-200/A
Poles	2
Protection degree	IP23
PTO speed (round/min)	430
Required tractor power	40 Hp
Length (mm)	805
Width (mm)	580
Height (mm)	915
Dry weight (Kg)	139
Silenced	No
Super silenced	No
Voltage regulator	Compound