



MASE MARINER 1750 KS SINGLE PHASE SILENCED MARINE GENERATOR 17.5 KW

Reference: MASE MARINER 1750 KS

MASE MARINER 1750 KS SILENCED SINGLE-PHASE MARINE GENERATOR 17.5 KW

MASE MARINER1750KS single phase silenced marine generator is equipped with a Kubota V2203 diesel engine capable of delivering a maximum power of 17.5 KW at 1500 rpm.

The MASE MARINER1750KS is built with and synchronous alternator, self-excited with air cooling, is extremely compact and powerful, also suitable on small boats.

The MASE MARINER1750KS allows easy access for maintenance of the fuel and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto shutdown for low oil pressure and high engine temperature or exhaust gas.

The alternator of the MASE MARINER1750KS is synchronous with 4 poles, self-regulated, self-excited, brushless, which in coupling with the powerful KUBOTA engine can deliver a maximum power of 17.5 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the one at home.

The MASE MARINER1750KS marine generator is equipped with a soundproof cabin that makes it super quiet, with a sound emission of 49 dB(A) at a distance of 7 m. The soundproof cabin in painted aluminum is extremely lightweight and of very high resistance to external agents.

TECHNICAL FEATURES MASE MARINER1750KS

Phase Type: Single Phase
Maximum Power: 17.5 KW
Continuous Use Power: 15.6 KW
Fuel: Diesel
Voltage: 115 - 230 V
Frequency: 50 Hz
Motor: Kubota V2203, 4 Stroke
Mechanical Power: 27.3 Hp
Number of Cylinders: 4
Displacement: 2197 cc
RPM Regulator: Mechanical Centrifugal
Engine RPM: 1500 rpm
Fuel Consumption: 6.1 l/h
Sound pressure: 49 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage regulator: AVR
Length: 1135 mm
Width: 631 mm

Height: 694 mm
 Weight: 465 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Maximum power single phase (KW)	17.5
Continuous power single phase (KW)	15.6
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	115 / 230
Engine	KUBOTA D1703, 4 Tempi
Engine rpm (rpm)	1500
Speed governor	Electronic
Engine capacity (cm ³)	2197
Number cylinders	4
Cooling	Air
Inyección	Indirect
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	6.2 at 100% of the load
Acoustic pressure	49 dB(A) at 7 m
Length (mm)	1135
Width (mm)	631
Height (mm)	694
Dry weight (Kg)	465
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes
Product type	Generator

Voltage regulator	AVR
Engine manufacturer	Kubota
Phase	Single phase
