



MASE MARINER 2200 KS SINGLE PHASE SILENCED MARINE GENERATOR 22 KW

Reference: MASE MARINER 2200 KS

MASE MARINER 2200 KS SILENCED SINGLE-PHASE MARINE GENERATOR 22 KW

MASE MARINER2200KS single phase silenced marine generator is equipped with a Kubota V2403 diesel engine capable of delivering a maximum power of 22 KW at 1500 rpm.

The MASE MARINER2200KS is built with and synchronous alternator, self-excited with air cooling, is extremely compact and powerful, suitable for small boats.

The MASE MARINER2200KS allows easy access for maintenance of the fuel and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high engine temperature or exhaust gas.

The alternator of the MASE MARINER2200KS is synchronous with 4 poles, self-regulated, self-excited, brushless, which in coupling with the powerful KUBOTA engine can deliver a maximum power of 22 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the one at home.

The MASE MARINER2200KS marine generator is equipped with a soundproof cabin that makes it super quiet, with a sound emission of 49 dB(A) at a distance of 7 m. The soundproof cabin in painted aluminum is extremely lightweight and of very high resistance to external agents.

TECHNICAL FEATURES MASE MARINER2200KS

Phase Type: Single Phase
Maximum output: 22 KW
Continuous Use output: 20 KW
Fuel: Diesel
Voltage: 115 - 230 V
Frequency: 50 Hz
Engine: Kubota V2403, 4 Stroke
Mechanical Power: 29.5 Hp
Number of Cylinders: 4
Displacement: 2434 cc
Engine RPM: 1500 rpm
Fuel Consumption: 6.1 l/h
Sound pressure: 49 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage regulator: AVR
Length: 1135 mm
Width: 631 mm
Height: 694 mm

Weight: 465 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	22
Continuous power single phase (KW)	20
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	115 / 230
Engine	Kubota V2403, 4 Tempi
Engine rpm (rpm)	1500
Speed governor	Electronic
Engine capacity (cm ³)	2434
Number cylinders	4
Cooling	Air
Inyección	Indirect
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	6.2 at 100% of the load
Acoustic pressure	49 dB(A) at 7 m
Length (mm)	1135
Width (mm)	631
Height (mm)	694
Dry weight (Kg)	465
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes
Product type	Generator

Voltage regulator	AVR
Engine manufacturer	Kubota
