



## MOSA GE SX-16000 KDM

Reference: CM5S1011

### MOSA GE SX-16000 KDM 14,4 KW

MOSA GE SX-16000 KDM singlephase 14,4 KW generator set with Kohler diesel engine. The MOSA GE SX-16000 KDM generator set is equipped with electric start. The alternator of the MOSA GE SX-16000 KDM generator set is synchronous and singlephase.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 372 kg as well as the practical central hook for lifting.

The MOSA GE SX-16000 KDM generator set with 38-liter fuel tank has a fuel consumption of 3,7 liters/hour at 75% load for an autonomy of more than 10 hours.

#### Sockets:

1 x 230V 63A 2P+T CEE IP67  
1 x 230V 32A 2P+T CEE IP67  
1 x 230V 16A 2P+T CEE IP67  
1 x 230V 16A 2P+T SCHUKO

#### Technical specifications MOSA GE SX-16000 KDM:

Maximum power Single-phase: 14.4 KW  
Single-phase continuous use power: 13 KW  
Maximum power Single-phase: 16 KVA  
Single-phase continuous use power: 14.5 KVA  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: Kohler KDW1003  
Starting: Electric  
Consumption: 3.7 Lt/h at 75% of the load  
Length: 1784 mm  
Width: 710 mm  
Height: 1115 mm  
Weight: 372 Kg  
Supersilenced

MOSA GE SX-16000 KDM portable generator set - Kohler diesel engine electric start - Singlephase alternator

If you are looking for another product such as MOSA GE SX-16000 KDM generator set then you can browse our catalog for more [terrestrial generator sets](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	14.4
Continuous power single phase (KW)	13
Maximum power single phase (KVA)	16
Continuous power single phase (KVA)	14.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 63A 2P+T CEE IP67 - 1 x 230V 32A 2P+T CEE IP67 - 1 x 230V 16A 2P+T CEE IP67 - 1 x 230V 16A 2P+T SCHUKO
Engine	KOHLER KDW702
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Alternator	Sincrono
Fuel tank capacity (L)	38
Consumption (L/h)	3.7
Running time (h)	10.5
Acoustic pressure	62 dB(A) at 7 m
Length (mm)	1784
Width (mm)	710
Height (mm)	1115
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Kohler