



MASE MARINER 1304 S SINGLE PHASE MARINE GENERATOR SILENCED 12KW

Reference: MARINER 1304 S

MASE MARINER 1304 S SILENCED SINGLE-PHASE MARINE GENERATOR 12KW

MASE MARINER1304S single-phase silenced marine generator is equipped with a YANMAR 3TNV88 diesel engine capable of delivering a maximum power of 12 KW at 1800 rpm.

The MASE MARINER1304S is built with and synchronous alternator, self-excited with air cooling, is extremely compact and powerful, suitable even on small boats. The alternator is complete with a voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like that of the house.

The MASE MARINER1304S allows easy access for maintenance of the power and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER1304S is equipped with a soundproof cabin that makes it super silent, with a sound emission of 54dB(A) at a distance of 7 m. The painted aluminum soundproof cabin is extremely lightweight and of very high resistance to external agents.

TECHNICAL FEATURES MASE MARINER1304S

Phase Type: Single Phase
Maximum Power: 12 KW
Fuel: Diesel
Voltage: 120 - 240 V
Frequency: 60 Hz
Motor: YANMAR 3TNV88, 4 Stroke
Mechanical Power: 20.4 Hp
Number of Cylinders: 3
Displacement: 1642 cc
Engine RPM: 1800 rpm
Fuel Consumption: 4 l/h
Sound Pressure: 54 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage Regulator: Yes
Length: 1040 mm
Width: 631 mm
Height: 694 mm
Weight: 344 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	12
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120 / 240
Engine	YANMAR 3TNV88
Engine rpm (rpm)	1800
Speed governor	Centrifugal, mechanical
Engine capacity (cm ³)	1642
Number cylinders	3
Cooling	Air
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	4 at 100% of the load
Acoustic pressure	53 dB(A) at 7 m
Length (mm)	1040
Width (mm)	631
Height (mm)	694
Dry weight (Kg)	344
Inverter	No
AVR	No
Compound	No
Silenced	Yes
Super silenced	Yes
Voltage regulator	YES