



FISCHER PANDA 8 MINI PVMV-N/PVM-NE VEHICLE GENERATOR 7.5KW

Reference: 0000374

FISCHER PANDA 8 MINI PVMV-N/PVM-NE VEHICLE GENERATOR 7.5KW

The generator FISCHER PANDA 8 MINI PVMV-N/PVM-NE VEHICLE GENERATOR 7.5KW single-phase is equipped with a KUBOTA Z482 engine with Diesel power supply, capable of delivering a maximum power of 7,5KW.

Veicular Generator is equipped with a silencer system completely integrated in the soundproof capsule. This solves most of the installation problems inside the vehicle, since the exhaust is already mounted.

The FISCHER PANDA generator must be installed with an external radiator. It is recommended to mount it on the roof or any other suitable location on the outside of the vehicle.

Equipment

Roof radiator rd3.3 tropical 120.1.50-60
Passatetto Dia 25 mm
Set 4 vibration dampers FPB 4 x BRB 70 A40 M12 SH 40
Exhaust elbow INOX with silicone joint
Diesel filter with water softener WS180

TECHNICAL FEATURES FISCHER PANDA PVMV-N AGT-DC

Single Phase Vehicular Generator
Rated Power: 7.5 kW
Continuous Power: 6.70 kW
Fuel: Diesel
Voltage: 120 V
Frequency: 60 Hz
Insulation Class: H
RPM: 3600 rpm
Permanent Magnets
Voltage Regulator: Capacitor
Power Factor Cos Pi: 1. 00
Engine KUBOTA Z482
Cylinders: 2
Displacement: 479 cm³
Power: Electric 12V (24V OPTIONAL)
Supersilenced: 52 dB(A) at 7 meters
Type of soundproofing cover: GFK (Glass fiber reinforced polyester)
Insulation material: 4DS

Length: 870 mm
Width: 580 mm
Height: 634 mm
Weight: 278 Kg

Are you looking for a generator with different characteristics? [Here](#) you can find the whole range of FISCHER PANDA generators or other specialized brands

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7.5
Continuous power single phase (KW)	6.7
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120
Engine	KUBOTA Z482, 4 stroke
Engine rpm (rpm)	3600
Starting system	Electric 12 Vcc
Engine capacity (cm ³)	479
Number cylinders	2
Cooling	Water
Motor insulation class	H
Acoustic pressure	52 dB(A) at 7 m
Length (mm)	870
Width (mm)	580
Height (mm)	635
Dry weight (Kg)	278
Silenced	Yes
Super silenced	Yes
PMG	Yes
Product type	Generator
Voltage regulator	Inverter
Engine manufacturer	Kubota