



ITALTOWER MT55 LIGHTING TOWER 4x160 W MULTILED

Reference: MT55_PRO02

ITALTOWER MT55 LIGHTER TOWER 4x160 W MULTILED

ITALTOWER MT55 4x160W is a manually lifted lighting tower equipped with 4 floodlights capable of delivering a light output of 160W each.

ITALTOWER MT55 4x160 is equipped with a galvanized steel lifting tower capable of extending up to a maximum height of 5.5 meters. The tower is complete with a hand pump for raising and manual locking on each extension to avoid the rotation of the same and to ensure the maximum extension of the column even in the absence of air inside.

ITALTOWER MT55 stands out for its performance, compactness and solidity, with its 4x160W LED, able to compete with much bulkier lighting towers equipped with a halogen system.

The ITALTOWER MT55 is suitable for a variety of large-scale construction work, maintenance repair, incident management and disaster relief work, high-brightness lighting needs.

The ITALTOWER MT55 4x160 is designed to be combined with a generator set and can be connected in series in order to use one generator for multiple lighting units.

The lightness of the ITALTOWER MT55 will also allow you to move it easily and thanks to the 4 feet, removable and foldable to optimize the space inside the container, you will be able to illuminate what you want.

ITALTOWER MT55 4x160 TECHNICAL FEATURES

Number of lights: 4
Lamps power: 160 W LED
Lumen: 81400 lm
Lit area: 2400 sqm
Voltage: 230 V
Frequency: 50 Hz
Consumption: 4 X 160W = 0. 64 KW
Maximum height: 5.5m
Lifting system: Manual
Wind resistance: 80 Km/h
Trolley: Stationary
Stabilizers: 4
Length (mm): 640
Width (mm): 355
Height (mm): 1920
Dry weight (Kg): 95

Light tower including 10 m cable and 2p+t 16 A socket

Looking for a light tower with different technical characteristics? [Here](#) you can find the full range of lighting towers ITALTOWER or other brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Maximum height (m)	5.5
Type of lamps	LED
Lamps	4 x 160 W
Telescopic pole	Vertical
Illuminated area (m ²)	2400
Total lumens (Lm)	81400
Lifting System	Manual lifting system
Open size (mm)	2200 x 2200 x 5700
Length closed (mm)	
Width closed (mm)	640
Height closed (mm)	
With generator / Without generator	Without generator
Transportability	Stationary
Stability to wind (Km/h)	80 Km/h
Weight (Kg)	95