



HONDA FJ 500 SE POWER TILLER 163cc

Reference: FJ 500 SE

HONDA FJ500SE COMPACT TILLER 163cc

HONDA FJ500SE is a compact tiller equipped with a HONDA GX160 4-stroke gasoline engine, capable of delivering a mechanical of 3.6 kW at 3600 rpm.

HONDA compact tiller FJ500SE is unbeatable in large gardens or on large plots of land, it proves to be a powerful tool with multiple possibilities, ideal for heavy duty use. The versatile HONDA compact tillers FJ500SE are as tough as a tractor, and have smart features that make them super easy to use.

Torque represents engine, and when you have a good powertrain there's plenty of it available, especially with a HONDA GX160 four-stroke engine. That's why these are perfect for the compact tiller, capable of performing many different functions.

HONDA FJ500SE Compact is surprisingly quiet for its 163 cc displacement, in fact it delivers a sound pressure of only 81 dB(A), also thanks to the high quality of materials vibration is minimized to give you the comfort of a solid and secure grip.

HONDA FJ500SE Compact Tiller TECHNICAL SPECIFICATIONS:

Maximum working width: 800 mm

Maximum working depth: 325 mm

Forward speed: 1

Reverse speed: 1

Forward rotation speed: 113 rpm

Reverse rotation speed: 28 rpm.

Engine: HONDA GX160, OHC 4-stroke

Fuel: Gasoline.

Engine displacement: 163 cc.

Engine: 3.6 kW /3600 rpm.

Engine net torque: 10.3 Nm / 2500 rpm.

Fuel tank capacity: 2.4 Lt.

Engine oil capacity: 0.58 Lt.

Start: Recoil start

Transmission clutch: Manual - Belt tension

Transmission: Constant gear

Final drive: Chain

Sound pressure to operator's ear: 81 dB(A)

Guaranteed sound power level: 96 dB(A)

Vibrations: 5.6 meters/second squared

Width: 1395 mm

Depth: 610 mm

Height: 980 mm
Dry weight: 57 Kg

The power tiller Compact FJ500SE is NOT complete with tiller.

Are you looking for a FJ500SE power tiller with different characteristics? [Here](#) you can find the full range of HONDA FJ500SE power tillers and other specialized brands

Technical Sheet

Fuel	Gasoline
Engine	Honda GX160, 4 stroke, OHV
Engine rpm (rpm)	3600
Starting system	Pull starter with recoil
Engine capacity (cm ³)	163
Working width (mm)	800
Transmission	Constant Gear
Acoustic pressure	81 dB(A)
Height (mm)	980