



## ITALTOWER TOWERLOOP PRO01 LIGHT TOWER 4x160W MULTILED

Reference: TWLOOP\_PRO01

### ITALTOWER TOWERLOOP PRO01 LIGHTER TOWER 4x160W MULTILED

ITALTOWER TOWERLOOP PRO01 is a light tower equipped with 4 led projectors 160W high brightness with directional optics and handles for easy rotation, with a lifting system that allows an extension up to 7 mt.

The ITALTOWER TOWERLOOP PRO01 light tower is supplied with a plug socket kit for the connection in series of several units up to a maximum of 6. The ITALTOWER TOWERLOOP PRO01 is supplied with galvanized guides and eyebolts for moving and lifting. These features make the operation by the operator very simple, making the unit easy to handle and use.

The efficient manual lifting system is able to bring the projectors to a height of 7 m, combined with 4 LED lamps, the light tower can illuminate an area of 2800 square meters with a maximum luminous intensity of 81400 lm.

The ITALTOWER TOWERLOOP PRO01 is equipped with 4 stabilizers which make the light tower resistant to strong wind gusts up to 100 km/h. ITALTOWER TOWERLOOP PRO01 is NOT equipped with an internal generator, but in return it can be effectively powered by an external source such as a generator set or can be connected directly to the power grid.

#### ITALTOWER TOWERLOOP PRO01 TECHNICAL FEATURES

Number of lights: 4  
Lamp power: 160 W multiLED  
Lumen: 81400 lm  
Lit area: 2800 mq  
Phase type: Single phase  
Voltage: 110 / 230 V  
Frequency: 50 Hz (60 hz ONLY ON REQUEST)  
Output: 230 V 16A  
Maximum height: 7 m  
Lifting system: Manual  
Rotation: 359°  
Wind resistance: 100 Km/h  
Trolley: Trolley with hand tow  
Stabilizers: 4  
Length (mm): min 930 - MAX 1800  
Width (mm): min 800 - MAX 1600  
Height (mm): min 2300 - Max 7000  
Dry weight (Kg): 235

Are you looking for a light tower with different characteristics? [Here](#) you can find the full range of light towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

## Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	110 / 220
Type of lamps	MULTILED
Lamps	4 x 160 W
Telescopic pole	Vertical
Illuminated area (m <sup>2</sup> )	2800
Total lumens (Lm)	81400
Lifting System	Manual lifting system
Maximum height (m)	7
Mast rotation	359°
Open size (mm)	
Length closed (mm)	930
Width closed (mm)	800
Height closed (mm)	2300
With generator / Without generator	Without generator
Transportability	Stationary
Stability to wind (Km/h)	100 Km/h
Weight (Kg)	235