



## ITALTOWER URANO PRO02 LIGHT TOWER 4x320 W MULTILED WITH HOMOLOGATED TROLLEY

Reference: URANO\_PRO02

### ITALTOWER URANO PRO02 LIGHTER TOWER 4x320 W MULTILED WITH APPROVED CART

ITALTOWER URANO PRO02 is a light tower with homologated trolley able to host a generator of 720 x 1680 mm, to power 4 Multiled Projectors of 320W each.

The ITALTOWER URANO PRO02 MULTILED is equipped with a manual lifting system, able to bring the tower to a height of 7 m. Thanks to the 4 LED lamps ITALTOWER URANO PRO02 is able to illuminate an area of 4300 square meters with a maximum luminous intensity of 166200 lm.

The main feature of this tower is the possibility to use any generator, of any brand, up to 720 x 1680 mm. This is thanks to 2 sliding bars that can be adjusted according to the size of the unit, making ITALTOWER URANO PRO02 an extremely flexible and versatile light tower. Moreover, thanks to its 4 stabilizers, the ITALTOWER URANO is safe and balanced in any situation, allowing you to always work in the best conditions.

ITALTOWER URANO PRO02 is easy to transport, ideal for night work on road construction sites. Equipped with all road approvals, they can be towed as a road trolley or transported by truck. Suitable for construction sites in remote areas without power grid and in urban centers where the 'public lighting is not sufficient.

#### TECHNICAL FEATURES ITALTOWER URANO PRO02

Number of lights: 4  
Lamps power: 320 W LED  
Lumen: 166200 lm  
Lit area: 4300 mq  
Voltage: 230 V  
Frequency: 50 Hz  
Consumption: 1,3 KW  
Maximum height: 7m  
Lifting system: Manual  
Rotation: 350°  
Wind resistance: 110 Km/h  
Trolley: HOMOLOGATED tow truck  
Tire size: 185/70R13  
Generator box: 720 x 1680 mm  
Stabilizers 4 + 1  
Length (mm): 2125  
Width (mm): 1202  
Height (mm): 2335

Dry weight (Kg): 340

Looking for a light tower with different features? [Here](#) you can find the full range of towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer

## Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Type of lamps	MULTILED
Lamps	4 x 320 W
Telescopic pole	Vertical
Illuminated area (m <sup>2</sup> )	4300
Total lumens (Lm)	166200
Lifting System	Manual lifting system
Maximum height (m)	7
Mast rotation	350°
Open size (mm)	2125 X 1202 X 7000
Length closed (mm)	2125
Width closed (mm)	1202
Height closed (mm)	2335
With generator / Without generator	Without generator
Transportability	Fast Trailer
Stability to wind (Km/h)	110
Weight (Kg)	340