



## GENMAC GR3500EiN SINGLE-PHASE 3.5 kW INVERTER GENERATOR

Reference: 39742

### GENMAC GR3500EiN SINGLE-PHASE GENERATOR 3.5 kW INVERTER

The GENMAC GR3500EiN Generator is equipped with an R210D-V engine powered by gasoline, is complete with **Inverter** voltage regulator and is capable of delivering a maximum power of 3.5KW.

The generator GENMAC GR3500EiN is equipped with electric start and manual recoil starter, is equipped with a tank of 8.3 liters has an autonomy of almost 5 hours. GENMAC GR3500EiN is compact, easy to maneuver and transport thanks to the practical folding sleeves and two wheels.

Thanks to the Inverter technology, the generator GENMAC GR3500EiN generates stabilized and very low distortion electricity, **ideal for powering electronic devices** (such as smartphones, computers, appliances, etc.) and allows you to vary the engine speed depending on the load applied, thus optimizing fuel consumption, exhaust emissions, noise and also increasing the life of the machine.

The GENMAC GR3500EiN is incredibly versatile and it is possible to use it in many fields of use, thanks to its **very low level of noise emission**, in fact the GENMAC GR3500EiN at full load emits up to **66 dBA @ 7m**.

#### TECHNICAL FEATURES GENMAC GR3500EiN:

Phase Type: Single-phase  
Nominal Power: 3.2 kW  
Maximum Power: 3.5 kW  
Frequency: 50Hz  
Nominal Voltage: 230V  
Voltage Regulator: Inverter  
Motor: R210D-Vi 4-stroke  
RPM: 3000 rpm  
Number of cylinders: 1  
Displacement: 212 ml  
Boosting: Manual / Electric  
Fuel: Gasoline  
Fuel tank capacity: 8.3 L  
Run time: 5.0 h  
Noise level: 66 dBA @ 7m.  
Length: 590 mm  
Width: 456 mm  
Height: 511 mm  
Weight: 45 kg

Are you looking for a power generator with different technical characteristics? [HERE](#) you can find generators or other specialized brands

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Continuous power single phase (KW)	3.2
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 Shucko + Thermal
Engine	4 Tempi
Engine rpm (rpm)	3000
Starting system	Electric and recoil
Number cylinders	1
Cooling	Air
Alternator	Sincrono
Fuel tank capacity (L)	8,2
Running time (h)	5 at 75% of the load
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	590
Width (mm)	456
Height (mm)	511
Dry weight (Kg)	45
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Inverter