



## AURORA LIGHT TOWER ALPHA Y-L 4X160 - S SLOW TOWING TROLLEY

Reference: ALPHA Y-L 4X160 - S

### AURORA TORRE FARO ALPHA Y-L 4X160 - S SLOW TOWER

AURORA ALPHA Y-L 4X160 - S is a light tower with generator equipped with Yanmar 2TNV70 diesel engine and manual hoisting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

AURORA ALPHA Y-L 4X160 - S is equipped with a galvanized steel lifting system capable of extending up to a maximum height of 8.5 meters, including 4 stabilization feet to secure the light tower once opened. The lifting system is operated manually and by a hydraulic system that allows the maximum extension without effort.

AURORA ALPHA Y-L 4X160 - S is complete with Yanmar 2TNV70 engine, these engines are super efficient with 1500 rpm. THE TOWERS FARO AURORA ALPHA Y-L 4X160 - S in addition guarantee you an autonomy of 180 h of work at 30% load.

The AURORA light tower lenses are equipped with extremely special optics designed specifically for the civil engineering and construction sectors. This innovative fully directional LED lens design ensures maximization of light spread and reduction of waste.

A single AURORA ALPHA can cover an area of 3300 m<sup>2</sup>, ensuring a brighter, safer and more productive site.

AURORA ALPHA comes complete with a slow moving trolley, this gives the customer the ability to easily transport the light tower.

#### TECHNICAL FEATURES AURORA ALPHA Y-L 4X160 - S

Manufacturer: Green Power  
Lights: 4 160W LEDs  
Lighted Area: 3300 Sq Ft  
Max Height: 8.5 Mt  
Lift: Manual  
Engine: Yanmar 2TNV70  
Emissions: Stage V  
Power supply: Diesel  
Engine speed: 1500 rpm  
Telescopic pole: Galvanized steel  
Wind resistance max: 100 Km/h  
Wind stability: nr 4 stabilizers  
Transport: Slow trolley  
Noise level at 7 mt: 70 dB (A)  
Total lumens: 81400 lm  
Voltage: 230V  
Frequency: 50 Hz  
Autonomy 30% load: 180 hr

Closed tower dimensions: 1154x1118x2430 mm  
Open tower dimensions: 2030x2202x8500 mm  
Dry weight: 560 Kg

Looking for a product with different characteristics? [Here](#) you can find the full range Green Power or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

## Technical Sheet

Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Starting system	Electric
Type of lamps	LED
Lamps	4 x 160W
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	3300
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	359°
Open size (mm)	2030x2202x8500 mm
Closed size (mm)	1154x1118x2430 mm
Dry weight (Kg)	560
Engine manufacturer	
Trailer type	traino lento