



CGM 180P-B200 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 180P-B200 AUTOMATICO

CGM 180P-B200 Single/three-phase 180KVA generator with automatic control panel

The CGM 180P-B200 is a single/three phase 180KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 180P-B200 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 180P-B200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 180P-B200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 30,7 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 180P-B200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 180P-B200 generator:

Phase type: Single-phase / Three-phase
Maximum three-phase power: 158.4 KW / 198 KVA
Three-phase continuous power: 144 KW / 180 KVA
Maximum single-phase power: 52.8 KW / 66 KVA
Single-phase continuous use power: 48 KW / 60 KVA
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Motor: PERKINS 1106A-70TAG3
Engine speed: 1500 rpm
Starting: Electric
Consumption: 30.7 Lt/h at 75% load
Length: 2400 mm
Width: 1100 mm
Height: 2000 mm
Weight: 1740 Kg
AVR

If you are looking for a product like the CGM 180P-B200 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Phase	Single phase / Three phase
Maximum power single phase (KW)	52.8
Continuous power single phase (KW)	48
Maximum power single phase (KVA)	66
Continuous power single phase (KVA)	60
Maximum power three phase (KW)	158.4
Continuous power three phase (KW)	144
Maximum power three phase (KVA)	198
Continuous power three phase (KVA)	180
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	Yanmar L70N
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	7010
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	105 x 135
Fuel tank capacity (L)	250
Consumption (L/h)	30.7
Running time (h)	2,5
Length (mm)	
Width (mm)	1100
Height (mm)	
Dry weight (Kg)	1740
Silenced	No
Super silenced	No
Product type	Generator

ATS Switch device

Optional ATS

Voltage regulator

AVR

Engine manufacturer

Perkins
