

CGM 500P-B750 WITH MANUAL CONTROL PANEL

Reference: CGM 500P-B750 MANUALE



CGM 500P-B750 Single/three-phase 500KVA generator with manual control panel

The CGM 500P-B750 is a single/three phase 500KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 500P-B750 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 500P-B750 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 500P-B750 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 76 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 500P-B750 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 500P-B750 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 440 KW / 550 KVA

Three-phase continuous power: 400 KW / 500 KVA

Maximum single-phase power: 146.67 KW / 183.33 KVA

Single-phase continuous use power: 133.33 KW / 166.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 2506A-E15TAG2

Engine speed: 1500 rpm

Starting: Electric

Consumption: 76 Lt/h at 75% load

Length: 3450 mm

Width: 1550 mm

Height: 2100 mm

Weight: 3930 Kg

AVR

If you are looking for a product like the CGM 500P-B750 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	146.67
Continuous power single phase (KW)	133.33
Maximum power single phase (KVA)	183.33
Continuous power single phase (KVA)	166.67
Maximum power three phase (KW)	440
Continuous power three phase (KW)	400
Maximum power three phase (KVA)	550
Continuous power three phase (KVA)	500
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	Perkins 2506A-E15TAG2
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	15200
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	137 x 171
Fuel tank capacity (L)	400
Consumption (L/h)	76
Running time (h)	15
Length (mm)	3450
Width (mm)	1550
Height (mm)	2100
Dry weight (Kg)	3930
Silenced	No
Super silenced	No
Product type	Generator

ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins
