



## CGM 350F-C450 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 350F-C450 AUTOMATICO

### CGM 350F-C450 Single/three-phase 350KVA generator super-silenced with automatic control panel

The CGM 350F-C450 is a single/three phase 350KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes the CGM 350F-C450 supersilenced. The CGM 350F-C450 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 350F-C450 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 55 litres per hour at 75% load. It also has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 350F-C450 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

#### Technical characteristics of the CGM 350F-C450 generator:

Phase type: Single-phase / Three-phase  
Maximum three-phase power: 308 KW / 385 KVA  
Three-phase continuous power: 280 KW / 350 KVA  
Maximum single-phase power: 102.67 KW / 128.33 KVA  
Single-phase continuous use power: 93.33 KW / 116.67 KVA  
Fuel: Diesel  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Motor: FPT CURSOR13 TE2A  
Engine speed: 1500 rpm  
Starting: Electric  
Consumption: 55 Lt/h at 75% load  
Length: 4300 mm  
Width: 1750 mm  
Height: 2350 mm  
Weight: 4140 Kg  
Super-silenced  
AVR

If you are looking for a product like the CGM 350F-C450 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	102.67
Continuous power single phase (KW)	93.33
Maximum power single phase (KVA)	128.3
Continuous power single phase (KVA)	116.67
Maximum power three phase (KW)	
Continuous power three phase (KW)	280
Maximum power three phase (KVA)	
Continuous power three phase (KVA)	350
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	FPT (IVECO) CURSOR 13TE2A turbo
Emissions Regulations	Stage 2
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	135 x 150
Fuel tank capacity (L)	400
Consumption (L/h)	55
Running time (h)	7.3
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	
Width (mm)	1750
Height (mm)	2350

Dry weight (Kg)	4140
AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco