



CGM e41Y-B50 WITH MANUAL CONTROL PANEL

Reference: CGM e41Y-B50 MANUALE

CGM e41Y-B50 Single/three-phase 41KVA generator with manual control panel

The CGM e41Y-B50 is a single/three phase 41KVA generator with a 1500 rpm Yanmar diesel engine, compact and easy to use, mounted on a fixed base. This CGM e41Y-B50 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM e41Y-B50 generator consists of a Linz, Stamford or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM e41Y-B50 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 8,5 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM e41Y-B50 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM e41Y-B50 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 36 KW / 45 KVA

Three-phase continuous power: 32.8 KW / 41 KVA

Maximum single-phase power: 12 KW / 15 KVA

Single-phase continuous use power: 10.93 KW / 13.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: YANMAR 4TNV98T-ZGECS

Engine speed: 1500 rpm

Starting: Electric

Consumption: 8.5 Lt/h at 75% load

Length: 1650 mm

Width: 850 mm

Height: 1650 mm

Weight: 665 Kg

AVR

If you are looking for a product like the CGM e41Y-B50 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	12
Continuous power single phase (KW)	10.9
Maximum power single phase (KVA)	15
Continuous power single phase (KVA)	13.67
Maximum power three phase (KW)	36
Continuous power three phase (KW)	
Maximum power three phase (KVA)	45
Continuous power three phase (KVA)	
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 63A 5P CEE - 1 x 230V 16A 3P CEE
Engine	Yanmar 4TNV98T-ZGECS
Emissions Regulations	STAGE 3A
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	3319
Number cylinders	4
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	98 x 110
Fuel tank capacity (L)	100
Consumption (L/h)	8.5
Running time (h)	11.8
Length (mm)	1650
Width (mm)	850
Height (mm)	1650
Dry weight (Kg)	665
AVR	Yes
Silenced	No
Super silenced	No

Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Yanmar
