



CGM 410S-C450 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 410S-C450 AUTOMATICO

CGM 410S-C450 Single/three-phase 410KVA generator super-silenced with automatic control panel

The CGM 410S-C450 is a single/three phase 410KVA generator with a 1500 rpm Scania diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of sound-absorbing material with high noise reduction, which makes the CGM 410S-C450 supersilenced.

The CGM 410S-C450 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 410S-C450 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 60 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 410S-C450 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 410S-C450 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 360.8 KW / 451 KVA

Three-phase continuous power: 328 KW / 410 KVA

Maximum single-phase power: 120.27 KW / 150.33 KVA

Single-phase continuous use power: 109.33 KW / 136.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: SCANIA DC13 072A 02 12

Engine speed: 1500 rpm

Starting: Electric

Consumption: 60 Lt/h at 75% load

Length: 4300 mm

Width: 1750 mm

Height: 2350 mm

Weight: 4220 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 410S-C450 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	120.27
Continuous power single phase (KW)	109.33
Maximum power single phase (KVA)	150.33
Continuous power single phase (KVA)	136.67
Maximum power three phase (KW)	360.8
Continuous power three phase (KW)	328
Maximum power three phase (KVA)	451
Continuous power three phase (KVA)	410
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	Scania DC13 072A 02 12
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	12700
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	130 x 160
Fuel tank capacity (L)	400
Consumption (L/h)	60
Running time (h)	2,5
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	
Width (mm)	1750
Height (mm)	2350

Dry weight (Kg)	4220
AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Scania
