



CGM 200DS-C200 WITH MANUAL CONTROL PANEL

Reference: CGM 200DS-C200 MANUALE

CGM 200DS-C200 Single/three-phase 200KVA generator super-silenced with manual control panel

The CGM 200DS-C200 is a single/three phase 200KVA generator with a 1500 rpm Doosan diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes the CGM 200DS-C200 supersilenced.

The CGM 200DS-C200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 200DS-C200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 32 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 200DS-C200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 200DS-C200 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 180 KW / 225 KVA

Three-phase continuous power: 160 KW / 200 KVA

Maximum single-phase power: 60 KW / 75 KVA

Single-phase continuous use power: 53.33 KW / 66.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: DOOSAN P086 T1

Engine speed: 1500 rpm

Starting: Electric

Consumption: 32 Lt/h at 75% load

Length: 3200 mm

Width: 1100 mm

Height: 2090 mm

Weight: 2330 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 200DS-C200 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	60
Continuous power single phase (KW)	53.33
Maximum power single phase (KVA)	75
Continuous power single phase (KVA)	66.67
Maximum power three phase (KW)	180
Continuous power three phase (KW)	160
Maximum power three phase (KVA)	225
Continuous power three phase (KVA)	200
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	DOOSAN P086 TI
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	111 x 139
Fuel tank capacity (L)	250
Consumption (L/h)	32
Running time (h)	7.8
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	3200
Width (mm)	1100
Height (mm)	2090

Dry weight (Kg)	2330
AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Doosan
