



## CGM DUAL20000SP THREE-PHASE GENERATOR 20,7KVA AVR STAGE V

Reference: DUAL 20000 SP

### CGM DUAL20000SP THREE-PHASE GENERATOR 20,7KVA AVR STAGE V

The CGM DUAL20000SP single-phase / three-phase Generator is equipped with OHV1000 Stage V gasoline engine, capable of delivering a power of 20,7KVA, complete with **Voltage regulator AVR**.

The CGM DUAL20000SP adapts perfectly to the most varied uses, thanks to the handling trolley that allows you to relocate it in perfect safety and simplicity. Thanks to the oversized 65-liter tank, this generator has an extraordinary autonomy of 6.6 hours at 75% load.

These CGM DUAL20000SP are equipped with high quality components, lightweight, compact, ease of use and also modern design, equipped with a practical electric start.

The alternator of CGM DUAL20000SP is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and AVR regulator.

#### The advantages of AVR voltage regulator

The automatic voltage regulator, or AVR allows the CGM DUAL20000SP to deliver stable energy and then be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for use at home, camping, hobby and leisure, but also for construction sites and craftsmen.

#### TECHNICAL FEATURES CGM DUAL20000SP

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Power: 20.7 KVA / 16.5 KW

Maximum ThreePhase Power: 20.7 KVA / 16.5KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Motor: OHV1000

Fuel: Gasoline

Motor RPM: 3000 rpm

Emission Standard: Stage V

Number of cylinders: 2

Displacement: 999 cc

Fuel tank capacity: 65 l

Consumption: 9.8 l @ 75%

Autonomy: 6.6 h

Alternator: Self-excited Brushless

Voltage regulator: AVR

Socket configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Width: 970 mm  
 Length: 680 mm  
 Height: 955 mm  
 Dry weight: 255 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the full range of CGM generators or other specialized brands

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	16.5
Maximum power single phase (KVA)	20,7
Maximum power three phase (KW)	16.5
Maximum power three phase (KVA)	20,7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Engine	OHV1000
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	999
Number cylinders	2
Alternator	Self-excited Brushless
Fuel tank capacity (L)	65
Consumption (L/h)	9.8 l @ 75%
Running time (h)	6.6 at 75% of the load
Length (mm)	970
Width (mm)	680
Height (mm)	
Dry weight (Kg)	
Silenced	No
Super silenced	No

---

Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	CGM

---