



CGM 275DS-B300 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 275DS-B300 AUTOMATICO

CGM 275DS-B300 Single/three-phase 275KVA generator with automatic control panel

The CGM 275DS-B300 is a single/three phase 275KVA generator with a 1500 rpm Doosan diesel engine, compact and easy to use, mounted on a fixed base. This CGM 275DS-B300 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 275DS-B300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 275DS-B300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 44 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 275DS-B300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 275DS-B300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 240 KW / 300 KVA

Three-phase continuous power: 220 KW / 275 KVA

Maximum single-phase power: 80 KW / 100 KVA

Single-phase continuous use power: 73.33 KW / 91.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: DOOSAN P126 TI

Engine speed: 1500 rpm

Starting: Electric

Consumption: 44 Lt/h at 75% load

Length: 2800 mm

Width: 1310 mm

Height: 1800 mm

Weight: 2640 Kg

AVR

If you are looking for a product like the CGM 275DS-B300 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	80
Continuous power single phase (KW)	73.33
Maximum power single phase (KVA)	100
Continuous power single phase (KVA)	91.67
Maximum power three phase (KW)	240
Continuous power three phase (KW)	220
Maximum power three phase (KVA)	300
Continuous power three phase (KVA)	275
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Terminal box
Engine	DOOSAN P126 TI
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	11051
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	123 x 155
Fuel tank capacity (L)	250
Consumption (L/h)	44
Running time (h)	5.7
Length (mm)	2800
Width (mm)	1310
Height (mm)	1800
Dry weight (Kg)	2640
AVR	Yes

Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Doosan
