



THREE-PHASE PTO GENERATOR 20 KVA AVR

Reference: PTO20

THREE-PHASE PTO GENERATOR 20 KVA AVR

THREE-PHASE PTO GENERATOR 20 KVA AVR is a cardan generator complete with MECC ALTE ECP28-M/4 alternator capable of delivering a power of 20KVA.

The THREE-PHASE PTO GENERATOR 20 KVA AVR shaft driven generator is very reliable as it has been built and designed using top quality materials. The PTO shaft generator is easy to transport, install and position due to the compact size, this model is ideal to be mounted on a tractor unit.

The THREE-PHASE PTO GENERATOR 20 KVA AVR has a required tractor power of 40 HP and a PTO speed of 430 rpm. These compact, rugged and easy-to-use generator sets come complete with a 3-point hitch base for secure attachment to any tractor.

TECHNICAL FEATURES THREE-PHASE PTO GENERATOR 20 KVA AVR:

Phase Type: Single phase / Three Phase
Continuous Power: 20 KVA
Continuous Power: 16 KW
Voltage: 400 - 230 V
Frequency: 50 Hz
Motor RPM: 1500 rpm
Tractor Power Required: 40 hp
PTO RPM: 430 rpm
Alternator: MECC ALTE ECP28-M/4
Voltage regulator: AVR
Length: 805 mm
Width: 580 mm
Height: 985 mm
Weight: 175 Kg

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Continuous power three phase (KW)	16
Continuous power three phase (KVA)	20

Frequency (Hz)	50
Voltage (V)	230 / 400
Engine rpm (rpm)	1500
Poles	4
Protection degree	IP23
PTO speed (round/min)	430
Required tractor power	29 KW / 40 HP
Length (mm)	805
Width (mm)	580
Height (mm)	985
Dry weight (Kg)	175
Silenced	No
Super silenced	No
Voltage regulator	AVR