



## MOSA TS 275 EVO INSTRUMENT THREE-PHASE MOTORWELDER 8 KVA STAGE V

Reference: C1SS0060BKP

### MOSA TS275 EVO INSTRUMENT THREE-PHASE MOTORWELDER 8 KVA STAGE V

MOSA TS275 EVO is a single-phase/three-phase motorwelder with a KOHLER KDW702 Stage V diesel engine, capable of delivering a maximum power of 8KVA.

MOSA TS275 EVO is a super-silenced motorwelder with a compact fairing, suitable for a wide range of applications including the construction of metal structures, oil pipelines and construction site use.

The MOSA EVO INSTRUMENT front panel incorporates a digital control that adds functionality for the user, including:

- Continuous control of current
- Continuous control of arc penetration
- Connector for remote control. Automatic changeover when connector is inserted
- Welding output sockets
- 2x Display
- 4 Digit
- Welding current setting
- Current and voltage measurement during welding
- VRD ON/OFF switch
- Connector for connection to Box PL400

With MOSA TS275 EVO, the user has the possibility not only of choosing the program but also of modifying it, customizing the machine according to his needs. The displays not only show the voltage and current during welding, but also allow them to be set beforehand.

#### TECHNICAL FEATURES MOSA TS275 EVO:

Phase Type: SinglePhase/ThreePhase

Maximum ThreePhase Power: 8 KVA / 6.4 KW

Maximum SinglePhase Power: 5 KVA / 5 KW

Voltage: 48 V / 110 V / 230 V / 400 V

Frequency: 50 Hz

Fuel: Diesel

Motor: KOHLER KDW702

Emission Standard: Stage V

Engine RPM: 3000 RPM

Adjustment Range: 20A / 20.8V ÷ 270A / 21V (Stick) | 20A / 10.8V ÷ 270A / 20.8V (Tig)

Service: 200A / 28V @ 100% - 230A / 29.2V @ 60% (Stick) | 200A / 18V @ 100% - 230A / 19.2V @ 60% - 270A / 20.8V @ 35% (Tig)

Trigger voltage: 66 VDC

Fuel tank capacity: 38 l

Fuel consumption: 2.5 Lt/h 60 % of load  
Run time: 15 h at 60 % of load  
Acoustic pressure: 95 dB(A) (70 dB(A) @ 7 m)  
Length: 1568 mm  
Width: 710 mm  
Height: 945 mm  
Dry weight: 390 Kg

Are you looking for a motorwelder with different technical characteristics? [Here](#) you can find the area dedicated to MOSA motorwelder or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	5
Maximum power single phase (KVA)	5
Maximum power three phase (KW)	6.4
Maximum power three phase (KVA)	8
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	48 / 110 / 230 / 400
Engine	Kohler KDW702
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Alternator	Asynchronous, three-phase, brushless
Open circuit voltage (V)	66
Fuel tank capacity (L)	38
Consumption (L/h)	2.5
Running time (h)	15
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1568
Width (mm)	710
Height (mm)	945
Dry weight (Kg)	390

---

Silenced	Yes
Super silenced	Yes
Engine manufacturer	Kohler

---