



## GREEN POWER GP 4000XM/KM SINGLE PHASE GENERATOR STAGE V 3,9KVA

Reference: 00007X

### GREEN POWER GP 4000XM/KM SINGLE PHASE GENERATOR STAGEV 3,9KVA

The Generator GREEN POWER GP 4000XM/KM single-phase is equipped with a KOHLER CH 270 **StageV** engine supplied by gasoline, and comes complete with capacitor voltage regulator (**AVR optional**).

GREEN POWER GP 4000XM/KM is equipped with manual recoil start with self-winding and has a low fuel consumption, in fact it consumes only 1,2 liter/hour at 75% load for a range of up to 3.4 hours of operation. Extremely practical sockets and controls facilitate the start-up and operation of the generator making these operations extremely simple and fast.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 48 kg as well as the practical tubular handles.

The GREEN POWER GP 4000XM/KM generator features an engine support system with a durable steel frame and rubber shock absorbers.

### STAGEV EMISSION STANDARDS

The STAGEV standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

### CARACTERISTICS

#### TECHNICAL FEATURES GREEN POWER GP 4000XM/KM

Phase type: Single phase  
Continuous use power: 3.5 KVA / 3.5 KW  
Maximum power: 3.9 KVA / 3.9 KW  
Engine: KOHLER CH 270  
Engine speed: 3000 rpm  
Emission regulation: StageV  
Starting: Manual recoil  
Fuel: Gasoline  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 2 x Schuko 16A 230V  
Tank capacity: 4 l  
Autonomy at 75% load: 3.4 h  
Consumption at 75% load: 1,2 Lt/h  
Length: 700 mm

Width: 570 mm  
 Height: 630 mm  
 Dry weight: 48 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.9
Continuous power single phase (KW)	3.5
Maximum power single phase (KVA)	3.9
Continuous power single phase (KVA)	3.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A SCHUKO
Engine	Kohler CH 270
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter with recoil
Engine capacity (cm <sup>3</sup> )	208
Number cylinders	1
Cooling	Air
Alternator	LINZ SP10 SE
Poles	2
Fuel tank capacity (L)	4
Consumption (L/h)	1.2 al 75% del carico
Running time (h)	3.4 at 75% load
Length (mm)	570
Width (mm)	700
Height (mm)	630
Dry weight (Kg)	48
Silenced	No
Super silenced	No

---

ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Kohler

---