



GENMAC POWERSMART G4000 SINGLE-PHASE GENERATOR 4KW AVR

Reference: 28343-B

GENMAC POWERSMART G4000 SINGLE-PHASE GENERATOR 4KW AVR

The generator GENMAC POWERSMART G4000 single-phase is powered by a gasoline engine and can deliver a maximum power of 4KW, including AVR voltage regulator.

The GENMAC POWERSMART G4000 generator features high quality components, is lightweight, compact, with a modern design and very easy to carry. The single-phase 4KW generator is equipped with a manual rope starter.

The GENMAC POWERSMART G4000 generator has been developed for any outdoor activity, from hobbyist to professional use; for this reason it reflects peculiar features and comfort that allow its reliability and convenience in the application areas. A convenient **contactor**, **fuel tank** for greater autonomy and **IP23 rain protection** for use in bad weather round off the standard equipment on the GENMAC POWERSMART G4000 generator.

The advantages of the AVR voltage regulator

The automatic voltage regulator, or **AVR**, enables the 4KW Genmac single-phase generator to deliver stable power and thus be able to connect equipment with delicate electronics such as computers, household appliances, smartphones and tablets: the generator set is therefore ideal for use at home, camping, hobbies and leisure, but also for construction sites and craftsmen. The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with safe and stabilized power.

TECHNICAL FEATURES GENMAC POWERSMART G4000:

Power supply: Gasoline
Synchronous alternator AVR
Single phase
Continuous power: 3.5KW
Continuous power: 3.5KVA
Maximum power: 4KW
Maximum power: 4KVA
Voltage: 230V
Frequency: 50 Hz
12Volt output: 8 A
Protection class: IP23
3000 rpm
Tank: 25 Lt.
Autonomy @ 75%: 13.3 h
Starting: manual recoil
Sockets: 2 schuko+thermal
1 output DC 12V + CB

Length (mm): 684
 Width (mm): 562
 Height (mm): 557
 Dry weight (Kg): 68
 Noise dB(A): 72 @ 7 m

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GENMAC generators or other specialized brands.

Images and technical data are not binding and may be subject to revisions.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	4
Continuous power single phase (KW)	3.5
Maximum power single phase (KVA)	4
Continuous power single phase (KVA)	3.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 SCHUKO + Thermal
Engine rpm (rpm)	3000
Ignition	Recoil
Starting system	Manuale
Number cylinders	1
Cooling	Air
Alternator	Sincrono
Protection degree	IP23
Fuel tank capacity (L)	25
Consumption (L/h)	
Running time (h)	13.3 at 75% of the load / 10 at 100% of the load
Acoustic pressure	72 dB(A) at 7 m
Length (mm)	684
Width (mm)	564
Height (mm)	557
Dry weight (Kg)	68
Silenced	No

Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR
