



GREEN POWER GP 8000XT/HE SINGLE/THREE PHASE STAGE V GENERATOR ELECTRIC START 7,7KVA

Reference: 00018X

GREEN POWER GP 8000XT/HE GENERATOR SINGLE-PHASE / THREE-PHASE STAGE V ELECTRICAL START 7,7KVA

The generator GREENPOWER GP 8000XT/HE single-phase / three-phase , is equipped with a HONDA GX390 **StageV** gasoline-powered engine, and is complete with Compound voltage regulator (**AVR optional**).

GREENPOWER GP 8000XT/HE is equipped with electric start and has a low fuel consumption, in fact it consumes only 2.1 liters/hour at 75% load for a range of up to 2.9 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 95 kg as well as the practical tubular handles. In addition, it is equipped with a practical and convenient electric start system, so that it can be put into operation quickly and easily.

The GREENPOWER GP 8000XT/HE generator is equipped with a high performance HONDA GX390 StageV engine that allows this machine to deliver a maximum threephase power of 7.7KVA.

VOLTAGE REGULATOR

The voltage regulator is an electronic device able to automatically regulate the voltage and eventually the frequency and/or the electric current according to set values. These values can be modified or bound to the technical characteristics of the regulator itself.

Basically, thanks to this device, the alternating current coming from the alternator is regulated and transformed into direct current at constant voltage.

The control panel of the GREENPOWER GP 8000XT/HE generator is composed of:

- Output sockets: 1x 230V 16A CEE / 1x 400V 16A CEE
- Thermal circuit breaker
- Voltmeter
- Three-pole magneto-thermal switch

TECHNICAL FEATURES GREENPOWER GP 8000XT/HE

Phase type: Singlephase/Threephase
Continuous use power Singlephase: 3.0 KVA / 2.4 KW
Maximum power Singlephase: 3.3 KVA / 2.7 KW
Continuous use power Threephase: 7.0 KVA / 5.6 KW

Maximum ThreePhase Power: 7.7 KVA / 6.2 KW
 Motor: HONDA GX390
 Engine RPM: 3000 rpm
 Emission Standard: Stage V
 Start: Electric
 Fuel: Gasoline
 Voltage: 230 / 400 V
 Frequency: 50 Hz
 Socket panel: 1 x CEE 16A 230V / 1 x CEE 16A 400V
 Tank capacity: 6. 1l
 Autonomy at 75% load: 2.9 h
 Consumption at 75% load: 2.1 Lt/h
 Length: 780 mm
 Width: 570 mm
 Height: 680 mm
 Dry weight: 95 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	2.7
Continuous power single phase (KW)	2.4
Maximum power single phase (KVA)	3.3
Continuous power single phase (KVA)	3
Maximum power three phase (KW)	6.2
Continuous power three phase (KW)	5.6
Maximum power three phase (KVA)	7.7
Continuous power three phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A CEE - 1 x 230V 16A CEE
Engine	Honda GX390
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico

Engine capacity (cm ³)	389
Number cylinders	1
Cooling	Air
Alternator	LINZ E1S10 MH
Poles	2
Fuel tank capacity (L)	6.1
Consumption (L/h)	2.1 at 75% of the load
Running time (h)	2.95 at 75% of the load
Length (mm)	780
Width (mm)	570
Height (mm)	680
Dry weight (Kg)	95
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Compound / AVR (optional)
Engine manufacturer	Honda