



## GREEN POWER GP 10000XM/HE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 10KVA

Reference: 00019X

### GREEN POWER GP 10000XM/HE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 10KVA

The generator GREENPOWER GP 10000XM/HE single-phase, is equipped with a HONDA GX630 **StageV** gasoline-supplied engine, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 10000XM/HE features a large 20-liter fuel tank and low fuel consumption, only 3.8 liters/hour at 75% load for up to 5.3 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The StageV generator is compact and convenient to maneuver and transport thanks to its compact size, as well as the practical tubular handles, and the possibility to have, as an **optional**, a trolley for fast and practical handling. In addition it is equipped with a practical and convenient electric start system, so that it can be put into operation in a simple and fast way.

The GREENPOWER GP 10000XM/HE generator is equipped with HONDA GX630 StageV engine that allows this machine to deliver a maximum single-phase power of 10KVA.

The voltage regulator is an electronic device able to automatically regulate the voltage and eventually the frequency and/or the electric current according to set values. These values can be modified or bound to the technical characteristics of the regulator itself. In essence, thanks to this device, the alternating current coming from the alternator is transformed into direct current at constant voltage.

### STAGEV EMISSIONS STANDARD

The STAGEV standard defines the guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the genset, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

The electric control panel of the GREENPOWER GP 10000XM/HE generator is composed of:

- Output sockets: 1x 230V 32A CEE / 1x 230V 16A CEE
- Thermomagnetic switch + differential
- Voltmeter
- Start key
- Voltmeter
- Low oil pressure led
- Mains presence led

TECHNICAL FEATURES GREENPOWER GP 10000XM/HE

Phase Type: Single Phase  
 Continuous Use Power: 9 KVA / 9 KW  
 Maximum Power: 10 KVA / 10 KW  
 Motor: HONDA GX630  
 Motor RPM: 3000 rpm  
 Emission Standard: StageV  
 Start: Electric  
 Fuel: Gasoline  
 Voltage: 230 / 400 V  
 Frequency: 50 Hz  
 Socket panel: 1 x CEE 16A 230V / 1 x CEE 32A 230V  
 Tank capacity: 20 l  
 Run time at 75% load: 5.3 h  
 Consumption at 75% load: 3.8 Lt/h  
 Length: 780 mm  
 Width: 570 mm  
 Height: 780 mm  
 Dry weight: 167 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	10
Continuous power single phase (KW)	9
Maximum power single phase (KVA)	10
Continuous power single phase (KVA)	9
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 32A CEE - 1 x 230V 16A CEE
Engine	Honda GX630, 4 stroke, OHV
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	688
Number cylinders	2
Cooling	Air
Alternator	MECC ALTE S20FS-160/A
Poles	2

Fuel tank capacity (L)	20
Consumption (L/h)	3.8 at 75 % of load
Running time (h)	5.3 at 75% of the load
Length (mm)	780
Width (mm)	570
Height (mm)	780
Dry weight (Kg)	167
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Honda