



## GREEN POWER GP 4000XM/YM SINGLE-PHASE DIESEL GENERATOR STAGEV 3,5KVA

Reference: 00102X

### GREEN POWER GP 4000XM/YM SINGLE-PHASE DIESEL GENERATOR STAGEV 3,5KVA

The generator GREENPOWER GP 4000XM/YM single-phase is equipped with a YANMAR L70AE **StageV** engine supplied by Diesel, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 4000XM/YM is equipped with manual recoil start with self winding and has a low fuel consumption, in fact it consumes only 1,2 liter/hour at 75% of load for a range of up to 3 hours of operation.

The GREENPOWER GP 4000XM/YM generator provides reliable power for home, work and recreation environments Safely appliances and other electronic devices Power solution for outdoor parties. Extremely convenient plugs and controls make starting and operating the generator easy and quick.

The GREENPOWER GP 4000XM/YM generator has a convenient double-curved handle for easy mobility and storage. GREENPOWER GP 4000XM/YM has a completely steel structure and a tank with a maximum capacity of 3,5 liters. The generator guarantees an efficient and silent operation thanks to the YANMAR L70AE StageV engine that allows to deliver a maximum power of 3,5KVA.

### STAGEV EMISSION STANDARD

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

#### TECHNICAL CHARACTERISTICS GREENPOWER GP 4000XM/YM

Phase Type: Single-phase  
Continuous duty power: 3.1 KVA / 3.1 KW  
Maximum power: 3.5 KVA / 3.5 KW  
Engine: YANMAR L70AE  
Engine speed: 3000 rpm  
Emission regulation: StageV  
Starting: Manual recoil  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 2 x Schuko 16A 230V  
Tank capacity: 3,5 l  
Autonomy at 75% load: 3 h  
Consumption at 75% load: 1,2 Lt/h  
Length: 700 mm

Width: 570 mm  
Height: 630 mm  
Dry weight: 69 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Continuous power single phase (KW)	3.1
Maximum power single phase (KVA)	3.5
Continuous power single phase (KVA)	3.1
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A SCHUKO
Engine	Yanmar L70AE, 4 stroke
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter with recoil
Engine capacity (cm <sup>3</sup> )	296
Number cylinders	1
Cooling	Air
Alternator	LINZ SP10 SE
Poles	2
Fuel tank capacity (L)	3.5
Consumption (L/h)	1.2 al 75% del carico
Running time (h)	3 al 75% del carico
Length (mm)	570
Width (mm)	700
Height (mm)	630
Dry weight (Kg)	69
Silenced	No
Super silenced	No

---

ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Yanmar

---