



GREEN POWER GP 6000XM/YM SINGLE-PHASE DIESEL GENERATOR STAGEV 5,5KVA

Reference: 00105X

GREEN POWER GP 6000XM/YM SINGLE-PHASE DIESEL GENERATOR STAGEV 5,5KVA

The generator GREENPOWER GP 6000XM/YM single-phase is equipped with a YANMAR L100AE **StageV** engine supplied by Diesel, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/YM is equipped with manual recoil start with self winding and has a low fuel consumption, in fact it consumes only 1,8 liter/hour at 75% of load for a range of up to 3 hours of operation.

The GREENPOWER GP 6000XM/YM generator provides reliable power for home, work and recreation environments Safely appliances and other electronic devices Power solution for outdoor parties. Extremely convenient plugs and controls make starting and operating the generator easy and quick.

The GREENPOWER GP 6000XM/YM generator has a convenient double-curved handle for easy mobility and storage. GREENPOWER GP 6000XM/YM has a completely steel structure and a tank with a maximum capacity of 5,5 liters. The generator guarantees an efficient and silent operation thanks to the YANMAR L100AE StageV engine that allows to deliver a maximum power of 5,5KVA.

STAGEV EMISSION STANDARD

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL CHARACTERISTICS GREENPOWER GP 6000XM/YM

Phase Type: Single-phase
Continuous Duty: 5 KVA / 5 KW
Maximum Power: 5.5 KVA / 5.5 KW
Engine: YANMAR L100AE
Engine RPM: 3000 rpm
Emission Regulation: StageV
Starting: Manual recoil
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x 16A 230V CEE
Tank capacity: 5.5 l
Autonomy at 75% of load: 3 h
Consumption at 75% of load: 1.8 Lt/h
Length: 780 mm

Width: 570 mm
Height: 680 mm
Dry weight: 94 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Technical Sheet

| | |
|-------------------------------------|--|
| Phase | Single phase |
| Maximum power single phase (KW) | 5.5 |
| Continuous power single phase (KW) | 5 |
| Maximum power single phase (KVA) | 5.5 |
| Continuous power single phase (KVA) | 5 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 |
| Sockets configuration | 1 x Schuko 16A 230V / 1 x 16A 230V CEE |
| Engine | Yanmar L100AE, 4 stroke |
| Emissions Regulations | Stage 5 |
| Engine rpm (rpm) | 3000 |
| Starting system | Pull starter with recoil |
| Engine capacity (cm ³) | 406 |
| Number cylinders | 1 |
| Cooling | Air |
| Alternator | LINZ SP10 MG |
| Poles | 2 |
| Fuel tank capacity (L) | 5.5 |
| Consumption (L/h) | 1.8 at 75% of the load |
| Running time (h) | 3 al 75% del carico |
| Length (mm) | 780 |
| Width (mm) | 570 |
| Height (mm) | 680 |
| Dry weight (Kg) | 97 |
| Silenced | No |

| | |
|---------------------|----------------------------|
| Super silenced | No |
| ATS Switch device | No ATS |
| Voltage regulator | Capacitor / AVR (optional) |
| Engine manufacturer | Yanmar |
