



GREEN POWER GP 4000XM/LE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

Reference: 00107X

GREENPOWER GP 4000XM/LE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

The generator GREENPOWER GP 4000XM/LE single-phase, is equipped with a KOHLER KD350 **StageV** Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 4000XM/LE is equipped with electric start and has a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of load for a range of up to 4 hours of operation.

The generator provides reliable power for home, work and recreational environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make starting and operating the generator easy and fast.

The GREENPOWER GP 4000XM/LE generator has a convenient double-curved handle for easy mobility and storage, has a completely steel structure and a tank with a maximum capacity of 4 liters. The generator guarantees an efficient and silent operation thanks to the KOHLER KD350 StageV engine with electric start, which can deliver a maximum power of 3.5KVA.

STAGEV EMISSION STANDARDS

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL FEATURES GREENPOWER GP 4000XM/LE

Phase Type: Single Phase
Continuous Use Power: 3.1 KVA / 3.1 KW
Maximum Power: 3.5 KVA / 3.5 KW
Motor: KOHLER KD350
Motor RPM: 3000 rpm
Emission Standard: StageV
Start: Electric
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 2 x Schuko 16A 230V
Tank capacity: 4 l
Autonomy at 75% load: 4 h
Consumption at 75% load: 1 Lt/h
Length: 780 mm

Width: 570 mm
 Height: 680 mm
 Dry weight: 80 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Continuous power single phase (KW)	3.1
Maximum power single phase (KVA)	3.5
Continuous power single phase (KVA)	3.1
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A SCHUKO
Engine	Kohler KD 350
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	315
Number cylinders	1
Cooling	Air
Alternator	LINZ SP10 SE
Poles	2
Fuel tank capacity (L)	4
Consumption (L/h)	1 at 75% of the load
Running time (h)	4 at 75% of the load
Length (mm)	780
Width (mm)	570
Height (mm)	680
Dry weight (Kg)	80
Silenced	No
Super silenced	No

ATS Switch device

Optional ATS

Voltage regulator

Capacitor / AVR (optional)

Engine manufacturer

Kohler
