



GREENPOWER GP 11000XM/LE SINGLE-PHASE DIESEL GENERATOR ELECTRIC START 11KVA

Reference: 00137X

GREENPOWER GP 11000XM/LE SINGLE-PHASE DIESEL GENERATOR ELECTRIC START 11KVA

The generator GREENPOWER GP 11000XM/LE single-phase, is equipped with a KOHLER KD425-2 engine supplied by Diesel, complete with capacitor voltage regulator (**AVR optional**) and electric start.

GREENPOWER GP 11000XM/LE features a roomy 7-liter fuel tank and low fuel consumption, only 2.5 liters/hour at 75% load for up to 2.8 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The alternator of the generator is the LINZ E1C11MB model (or equivalent primary brand) and is synchronous, single phase, with brushes and with class H insulation, in addition it is equipped with a voltage regulator. The generator is gifted with a practical electric start system, so that you can start the unit without any effort.

One of the main features of the generator is the motor/alternator coupling in mono-support through cone, on electro-welded steel base with interposition of vibration dampers.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 162 kg as well as the practical tubular handles. In addition, it is equipped with a practical and convenient electric starting system.

The GREENPOWER GP 11000XM/LE generator is equipped with a high performance KOHLER KD425-2 engine that allows this machine to deliver a maximum single-phase power of 11KVA.

The electric control panel of the GREENPOWER GP 11000XM/LE is composed of:

- Thermomagnetic circuit breaker
- Sockets: 1 x 32A 3P 230V / 1 x 16A 3P 230V
- Voltmeter
- Hour meter
- Ammeter
- Frequency meter
- Low oil pressure led
- Mains presence led

TECHNICAL FEATURES GREENPOWER GP 11000XM/LE

Phase type: Single phase
Continuous use power: 8.8 KVA / 8.8 KW
Maximum power: 11KVA / 11 KW
Motor: KOHLER KD425-2

Motor speed: 3000 rpm
 Emissions standard: NOT Emitted
 Start: Electric
 Fuel: Diesel
 Voltage: 230 V
 Frequency: 50 Hz
 Socket panel: 1 x 32A 3P 230V / 1 x 16A 3P 230V
 Tank capacity: 7 l
 Run time at 75% load: 2.8 h
 Consumption at 75% load: 2.5 Lt/h
 Length: 1060 mm
 Width: 620 mm
 Height: 780 mm
 Dry weight: 162 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	11
Continuous power single phase (KW)	8.8
Maximum power single phase (KVA)	3.6
Continuous power single phase (KVA)	8.8
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 32A 3P 230V / 1 x 16A 3P 230V
Engine	Kohler KD 425/2
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	954
Number cylinders	2
Cooling	Air
Alternator	LINZ E1C11MB
Poles	2
Fuel tank capacity (L)	7

Consumption (L/h)	2.5 al 75% del carico
Running time (h)	2.8 at 75% of the load
Length (mm)	1060
Width (mm)	620
Height (mm)	780
Dry weight (Kg)	162
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Kohler