



## FINI BK 119-500F-7,5-AP HIGH PRESSURE COMPRESSOR 7,5 HP

Reference: BRTN801FNM875

### FINI BK 119-500F-7,5-AP HIGH PRESSURE COMPRESSOR 7,5 HP

FINI BK 119-500F-7,5-AP is a high pressure compressor, equipped with a three-phase BK119 pump, capable of delivering a mechanical power of 7,5 Hp.

The Fini compressor is composed of powerful pumping groups that guarantee very high efficiency and reliability at the highest levels, capable of generating a pressure of 14 bar.

The FINI BK 119-500F-7,5-AP compressor combines a powerful and reliable group with a large air reserve, with a tank cable to contain up to 500 l of air, this makes this compressor suitable for all pneumatic accessories that require a high air consumption.

FINI BK 119-500F-7,5-AP is a two-cylinder lubricated belt-driven compressor, complete with electromechanical pressure switch with thermal relay protection.

FINI BK 119-500F-7,5-AP pumping group is equipped with large manifolds for a better cooling, complete with large size anti-vibration feet for a better stability during operation.

#### TECHNICAL SPECIFICATIONS FINI BK 119-500F-7,5-AP

Power supply phase: Three phase  
Power supply voltage: 400 V  
Power supply frequency: 50 Hz  
Pump: BK119  
Tank capacity: 500 l  
RPM: 1045 RPM  
Power: 5,5 KW - 7,5 HP  
Air output: 705 Lt/min - 24.9 cfm  
Pressure: 14 bar - 203 psi  
BSP: 2"  
Length: 2010 mm  
Width: 650 mm  
Height: 1330 mm  
Dry weight: 266 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to FINI compressors or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Three phase
Frequency (Hz)	50
Voltage (V)	400
Engine rpm (rpm)	1045
Power (KW)	5.5
Air output (L/min)	705
Mechanical power (hp)	7.5
Length (mm)	2010
Width (mm)	650
Height (mm)	1330
Dry weight (Kg)	266
Tank Capacity (l)	500