



BADA TM20 100% STAINLESS STEEL MANUAL PALLET TRUCK 2000KG

Reference:

BADA TM20/S/T MANUAL PALLET TRUCK STAINLESS STEEL CAPACITY 2000 Kg

The BADA TM20/S/T pallet truck in AISI 304 stainless steel has been designed for use in humid and corrosive environments where impeccable cleaning and hygiene are required and to solve corrosion problems associated with the use of acids and saline solutions.

Thanks to its construction characteristics, and the construction entirely in **AISI 304 stainless steel**, the pallet truck can be used in the food, chemical and pharmaceutical industries.

BADA TM20/S/T is resistant, easy to handle and with an ergonomic design, it fully responds to the most stringent hygienic requirements as it can be sanitized with regular high pressure washing.

BADA TM20/S/T is a pallet truck built entirely in AISI 304 stainless steel (including the lifting pump and hydraulic components), and is equipped with waterproof bearings and bushings built in polyamide material as required by the food industry.

BADA TM20/S/T **ON EXPLICIT REQUEST OF THE CUSTOMER** can be supplied in AISI 316 stainless steel (**Optional WITH surcharge**).

TECHNICAL CHARACTERISTICS BADA TM20/S/T

Type of propulsion: Manual
Drive system: Manual
Lifting: Manual
Construction material: AISI 304 stainless steel
Capacity: 2000 Kg
Quantity of rear wheels : 1 (2 optional)
Quantity of front wheels: 2
Lifting height: 115 mm
Fork width: 165 mm
Fork length: 1150 mm
Turning radius : 1280 mm
Closed upright height: 1215 mm
Total length: 1500 mm
Total width: 530 mm
Dry weight: 80 Kg

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to BADA or other Transpallet specialized brands.

Images and technical data are not binding.

Technical Sheet

Drive	Manual
Operator type	Manuale
Load capacity (Kg)	2000
Service weight (Kg)	80
Tyres: front wheels	POLY.I. / NYLON
Tyres: rear wheels	POLY.I. / NYLON
Quantity rear wheels	2
Quantity front wheels	1 (2 Optional)
Rear balancing axle	No
Lift height (mm)	115
Height of tiller in drive position max (mm)	1215
Height lowered (mm)	85
Overall length (mm)	1500
Overall width (mm)	530
Thickness fork (mm)	50
Width fork (mm)	165
Lenght fork (mm)	1150
Distance between fork arms (mm)	190
Turning radius (mm)	1280
Weigher	No
Type of lifting	Manual