



## THREE-PHASE PTO GENERATOR 87.5KVA AVR

Reference: GP00815

### THREE-PHASE PTO GENERATOR 87.5KVA AVR

PTO Generator Three-phase, equipped with MECC ALTE ECP34-1S/4 alternator capable of delivering a power of 87.5KVA, complete with **AVR voltage regulator**.

The generator is very reliable as it has been built and designed using top quality materials. The generator is easy to transport, install and position due to its compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 180 HP and a PTO speed of at least 420 rpm. The minimum parameters indicated are necessary for the correct functioning of the PTO generator, if they are not respected it is possible to cause malfunctions of the equipment.

The generator is equipped with an electrical panel complete with:

- Thermomagnetic circuit breaker
- Differential switch
- 125 A 400 V socket
- 32 A 230 V socket
- 16 A 230 V Schuko
- E31 digital module complete with: Voltmeter, Frequency meter and Hour meter

#### TECHNICAL FEATURES

Phase Type: Three Phase  
Continuous output: 87.5 KVA  
Continuous output: 70 KW  
Voltage: 230 - 400 V  
Frequency: 50 Hz  
Motor revolutions: 1500 rpm  
Tractor power required: 180 hp  
PTO revolutions: 420 rpm  
Alternator: MECC ALTE ECP34-1S/4 (OR EQUIVALENT)  
No. of poles: 4  
Insulation class: H  
Protection class: IP 23  
Voltage regulator: AVR  
Length: 1140 mm  
Width: 750 mm  
Height: 1210 mm  
Weight: 506 Kg

Are you looking for a PTO generator with different technical characteristics? [Here](#) you can find the full range of top quality brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Phase	Three phase
Continuous power three phase (KW)	70
Continuous power three phase (KVA)	87.5
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine rpm (rpm)	1500
Alternator	MECC ALTE ECP34-1S/4
Poles	4
Protection degree	IP23
PTO speed (round/min)	420
Required tractor power	180 HP
Length (mm)	1140
Width (mm)	750
Height (mm)	1210
Dry weight (Kg)	506
Silenced	No
Super silenced	No
Voltage regulator	AVR