



GENERATOR SUPERSILENCED 9,5KVA 50/60 Hz SINGLE-PHASE / THREE-PHASE AUTOMATIC PANEL

Reference: GD95KVAMT

GENERATOR SUPERSILENCED 9,5KVA 50/60 Hz SINGLE-PHASE / THREE-PHASE AUTOMATIC PANEL

The generator single-phase / three-phase is equipped with a YANMAR 3TNV76 diesel supplied engine, capable of delivering a power of 9,5KVA with automatic starting panel.

This generator is equipped with **electric start, manual or automatic** with 12 V battery, with automatic panel and **COMAP IL4 AMF9** control unit which allows you to view all electrical parameters of the engine and generator, of the functions, states of the Generator, manage the entire group and view, in case they occur, the errors or alarms of the system. In addition, this generator is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

AUTOMATIC TRANSFER SWITCH ATS

The Generator is designed for the use of an ATS automatic transfer switch. Thanks to which you will no longer have to worry about blackouts because if it goes off the power grid this panel is able to automatically start the group and will allow you to continue your business without losing your work data.

The Generator has a low fuel consumption, in fact it consumes only 2 liters / hour at 75% of the load, combined with a large tank of 70 liters of maximum capacity, it will give you an autonomy of about 35 hours.

The generator guarantees efficient and silent operation thanks to the motor YANMAR 3TNV76 engine, which allows to deliver a maximum power of 9.5KVA.

TECHNICAL FEATURES

Type of phase: Singlephase / Threephase
Power for continuous use 50 Hz: 8.7 KVA / 7 KW
Maximum power 50 Hz: 9.5 KVA / 7.7 KW
Power continuous use 60 Hz: 10 KVA / 8 KW
Maximum power 60 Hz: 11 KVA / 8.8 KW
Engine: YANMAR 3TNV76
Emissions standard: Not issued
Engine revs: 1500/1800 rpm
Starting: Electric / Automatic
Fuel: Diesel
Voltage available at terminals (V): 230/400/265/460
Frequency: 50/60 Hz
Voltage regulator: COMPOUND

Socket board: 1 x CEE 16A 400V 5P / Terminal block
Tank capacity: 70 l
Autonomy at 75% of the load: 35 h
Consumption at 75% of the load: 2 Lt / h
Acoustic pressure: 65 dB (A) @ 7 m
Length: 1750 mm
Width: 700 mm
Height: 1125 mm
Dry weight: 450 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to specialized brand generators.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	7,7 (50Hz) / 8,8 (60Hz)
Continuous power three phase (KW)	7 (50Hz) / 8 (60Hz)
Maximum power three phase (KVA)	9,5 (50Hz) / 11 (60Hz)
Continuous power three phase (KVA)	8,7 (50Hz) / 10 (60Hz)
Fuel	Diesel
Frequency (Hz)	50 / 60
Voltage (V)	230 / 400 / 265 / 460
Engine	YANMAR 3TNV76
Engine rpm (rpm)	1500 / 1800
Speed governor	Mechanical
Starting system	Electric / Automatic
Engine capacity (cm ³)	1116
Number cylinders	3
Cylinders' position	In line
Cooling	Water
Protection degree	IP21
Fuel tank capacity (L)	70
Consumption (L/h)	2 at 75% of the load
Running time (h)	35 at 75% load
Length (mm)	1750
Width (mm)	700
Height (mm)	1125
Dry weight (Kg)	450

Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Compound
