



PTO Generator Single Phase 18 kVA/ Three Phase 45 kVA AVR

Reference: 113911-NB

PTO Generator Single Phase 18 kVA/ Three Phase 45 kVA AVR

- For outdoor applications (field and home), in case of blackouts and in areas not served by the power grid
- Supplied with multiplier kit and protection, support with 3-point attachment (patented design), electrical panel with multifunction digital display for real-time data reading (voltmeter, frequency meter, ammeter, hour meter)
- Durability over time and maximum protection (thermal-magnetic and differential)
- Warranty 12 months
- Easy packaging and storage

Technical Features

Phase: Single / Three Phase
RPM: 1500
Required tractor power (Hp): 124
Single-phase power (kVA): 18
Three-phase power (kVA): 45
Pto Speed (rpm): 430
Voltage (V): 230 / 400
Frequency (Hz): 50
Lenght (mm): 1135
Width (mm): 640
Height (mm): 915
Weight (Kg): 258
AVR

Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	14.4
Maximum power single phase (KVA)	18
Maximum power three phase (KW)	36
Maximum power three phase (KVA)	45

Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	
Engine rpm (rpm)	1500
Protection degree	IP23
PTO speed (round/min)	430
Minimum tractor output (HP)	124
Transmission ratio	1 : 3.5
Length (mm)	1135
Width (mm)	640
Height (mm)	915
Dry weight (Kg)	258
Brushes	No
Voltage regulator	AVR