



ECOFLOW DELTA MINI PORTABLE BATTERY 2.1 KW REMOTE CONTROL

Reference: CAD00110 /

ECOFLOW DELTA MINI PORTABLE BATTERY 2.1 KW REMOTE CONTROL

The ECOFLOW DELTA MINI battery is a practical solution to have access, in any situation, to a very quiet energy source with zero CO₂ emissions.

Unlike generator the ECOFLOW DELTA MINI Portable Battery **does not require fuel** such as gasoline or diesel to power it. The ECOFLOW DELTA MINI can be recharged easily through a battery charger, through solar power, or through your car, RV, truck, etc.

ECOFLOW DELTA MINI can perform a full charge in 3/6 hours, absorbing up to 300 W from the solar panels (Optional). By recharging the battery with the home network it is possible to complete the charging cycle, going from 0-100% in 1.6 hours.

Thanks to the dedicated app, it is possible to remotely control the state of charge, the power supplied instant by instant and the primary functions of the portable battery. You can download the app for both [Android](#) and for [ios](#), easy to install, features a guide on correct use.

ECOFLOW DELTA MINI TECHNICAL FEATURES:

ENTRANCES

AC charging voltage: 220-240 VAC
AC power: X-Stream 900 W
Solar input: 300 W, 11-75 Vdc 10A
Car charger input: 12 V / 24 Vdc 8 A

EXITS

n° 2 AC Schuko outputs: 1.4 KW continuous, 2.1 KW peak, 220-240 Vca, 50 Hz / 60 Hz
n° 2 USB-A outputs: 12 W per port, 5 Vdc, 2.4 A
n° 1 USB-A for fast charging: 18 W 5 V DC, 2.4 A / 9V DC, 2 A / 12 V DC, 1.5 A
n° 1 USB-C output: 100 W 5 V / 9 V / 12 V / 15 V / 20 Vdc, 5 A
n° 1 auto output: 126 W 12.6 V DC, 10 A
n° 2 outputs DC5521: 12.6 V DC, 3 A

GENERAL INFORMATION

Solar charge connector: MC4
Max solar input power: 300 W
Capacity: 882 Wh
Cell type: lithium ion
Life cycle: 800 cycles

Width: 378 mm
Length: 184 mm
Height: 240 mm
Weight: 10.7 kg

Looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to EcoFlow Portable Batteries and Uninterruptible Power Supplies or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.1
Continuous power single phase (KW)	1.4
Maximum power single phase (KVA)	2.1
Maximum power three phase (KW)	1.4
Battery capacity (Wh)	882
Length (mm)	378
Width (mm)	184
Height (mm)	240
Weight (Kg)	10.7
Inputs	AC charging power: X-Stream 900 W / Solar input: 300 W, 11-75 Vdc 10A / Car charger input: 12 V/24 Vdc 8 A
Outputs	2 x AC Schuko outputs / 2 x USB-A outputs: 5 Vdc, 2.4 A / 1 x USB-A for fast charging: 18 W max, 12 V DC, 1.5 A / 1 x USB-C output: 20 Vdc, 5 A / 1 x auto output: 12.6 V DC, 10 A / 2 x DC5521 outputs: 12.6 V DC, 3 A
Life span	800