



ECOFLOW DELTA PORTABLE BATTERY 3,3 KW SOLAR CHARGING

Reference: CAE00110 /

ECOFLOW DELTA PORTABLE BATTERY 3,3 KW SOLAR CHARGING

The ECOFLOW DELTA Portable Battery is a practical solution for having access, in any situation, to an ultra-quiet, zero-carbon power source.

ECOFLOW DELTA is a portable battery with a huge capacity of 1.2 kWh, this guarantees hours of reserve power. The large inverter load of the ECOFLOW DELTA portable battery can also support DIY tools up to 1800 W (3300 W peak, pure sine wave).

The ECOFLOW DELTA can be recharged in multiple ways to suit any situation. Solar charging, car charging and more is also a portable solar power station. With EcoFlow panels, full charging takes only 4 hours. Power up to 11 devices simultaneously via AC, DC or USB outlets. Ideal as an emergency power pack in case of energy outages.

ECOFLOW DELTA TECHNICAL FEATURES:

INPUT

AC voltage: 220-240 VAC
AC power: 1200 W
Solar input: 400 W, 11-65 Vdc 10A
Car charger input: 12 V / 24 Vdc 8 A

OUTPUT

n° 4 AC Schuko outputs: 1,8 KW continuous, 3,3 KW peak, 220 Vca, 50 Hz
n° 2 USB-A: 12 W per port, 5 Vcc, 2,4 A
n° 2 USB-A for fast charging: 18 W 5 Vcc, 2,4 A / 9Vcc, 2 A / 12 Vcc, 1,5 A
n° 2 USB-C: 60 W 5/9/12/15/20 Vcc, 3 A
n° 1 car output: 108.8 W 13.6Vcc, 8 A

GENERAL INFORMATION

Solar charge connector: MC4
Capacity: 1260 Wh
Cell type: Lithium Ion
Life cycle: 800 cycles
Width: 400 mm
Length: 210 mm
Height: 270 mm
Weight: 14 kg

Looking for a Portable Batteries with different technical characteristics? [HERE](#) you can find the Portable Batteries and UPS or other specialized brands.

Images and technical data are not binding and may be subject to revision by the manufacturer

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.3
Continuous power single phase (KW)	1.8
Maximum power single phase (KVA)	3.3
Maximum power three phase (KW)	1.8
Battery capacity (Wh)	1260
Length (mm)	400
Width (mm)	210
Height (mm)	270
Weight (Kg)	14
Video	nGXtkcd-CJY
Inputs	AC AC charging power: 1200 W / Solar input: 400 W, 11-65 Vdc 10A / Car charger input: 12 V/24 Vdc 8 A power: 2875 W / Solar input: 1600 W, 11-150 Vdc 15A / Car charger input: 12 V/24 Vdc 8 A
Outputs	4 x AC Schuko outputs / 2 x USB-A outputs: 5 Vdc, 2.4 A / 2 x USB-A for fast charging: 12 VDC, 1.5 A / 2 x USB-C output: 20 Vdc, 3 A / 1 x auto output: 12.6 VDC, 10 A
Life span	800