

ECOFLOW RIVER MINI WIRELESS PORTABLE BATTERY 600 W SOLAR CHARGING



Reference: CAH00110 /

ECOFLOW RIVER MINI WIRELESS PORTABLE BATTERY 600 W SOLAR CHARGING

The ECOFLOW RIVER MINI WIRELESS Portable Battery is a practical solution to have access, to a light, powerful and zero-carbon energy source.

ECOFLOW RIVER MINI is incredibly small and lightweight, you can carry it in your hand or in a backpack. With a power output of 300 W (600 W peak), ECOFLOW RIVER MINI is ideal for 99% of devices: laptops, lights, TVs, and more. Not only is it made to last with a rugged, one-piece construction. It also features an advanced BMS for voltage, current and temperature protection.

The ECOFLOW RIVER MINI WIRELESS Portable Battery supports solar charging, ideal for camping and outdoor life. It supports up to 100 W of solar power and fully recharges in 3-6 hours. Make sure your solar panel has these features: 11-39V, 8A, up to 100W.

With X-Stream charging technology, ECOFLOW RIVER MINI recharges to 80% in one hour. Much faster than your powerbank, all in a battery with about 6 times the capacity. Recharge with solar power or via your car when you are on the road.

The portable battery has all the ports and outlets you need. 1 AC wall outlet, 1 DC car outlet, 3 USB-A ports and one USB-C fast charging port. With this device, you will have more ports than a power bank in a battery that fits in your hand.

TECHNICAL FEATURES ECOFLOW RIVER MINI WIRELESS:

INPUT

AC charging voltage: 220-240 VAC
AC charging power: 300 W
Solar input: 100 W, 11-39 Vdc 8 A
Car charger input: 12 V / 24 Vdc 8 A

OUTPUT

n°1 AC outputs: 300 W continuous, 600 W peak, 220 Vca, 50 Hz
n°3 USB-A: 12 W, 5 Vcc, 2,4 A
n°1 USB-C: 100W max.; 5 V / 9 V / 12 V / 15 V / 20 V, 5 A
n°1 auto output: 126 W 12.6 Vcc, 10 A
n°1 wireless output: 15W

GENERAL INFORMATION

Solar charge connector: MC4
Capacity: 210 Wh
Cell type: Lithium Ion

Life cycle: 800 cycles
Width: 249 mm
Length : 140 mm
Height: 133 mm
Weight: 2.85 kg

Looking for a Portable Batteries with different technical characteristics? [HERE](#) you can find the area dedicated to EcoFlow Portable Batteries and UPS or other specialized brands.

Images and technical data are not binding and may be subject to revision by the manufacturer

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	0.6
Continuous power single phase (KW)	0.3
Maximum power single phase (KVA)	0.6
Maximum power three phase (KW)	0.3
Battery capacity (Wh)	210
Length (mm)	249
Width (mm)	140
Height (mm)	133
Weight (Kg)	2.85
Video	gRlqMXwHKBg
Inputs	AC charging power: 300 W / Solar input: 100 W, 11-39 Vdc 8A / Car charger input: 12 V/24 Vdc 8 A
Outputs	1 x AC outputs / 3 x USB-A outputs: 5 Vdc, 2.4 A / 1 x USB-C: 5-9-12-15-20V, 5A / 1 x auto output: 12.6 VDC, 10 A / 1 x wireless output: 15W
Life span	500